

LEGEND:

= 90° SYMBOL

= AS-DRILLED WELLHEAD.

= TOP OF GAS INTERVAL.

= BOTTOM HOLE.

= SECTION CORNERS LOCATED. (NAD 83)

= SECTION CORNERS RE-ESTABLISHED. (Not Set on Ground.) (NAD 83)

T6S, R97W, 6th P.M.

1917 Brass Cap,
1.0' High
Lat: 39.501243°
Long: 108.196735°

S89°54'51"E - 2633.48' (Meas.)

S89°56'54"E - 2638.99' (Meas.)

1917 Brass Cap,
0.6' High, Steel Post
Lat: 39.501239°
Long: 108.178056°

2322'

(AS-DRILLED)
PUCKETT 25A-26-697
Elev. Graded Ground = 8322.4'

26

WELLBORE

1694'

2402'

2285'

Top of Gas Interval

Bottom Hole

724'

768'

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486764°
Long: 108.178042°

S 1/4 Cor. Sec. 25,
1920 Brass Cap,
2.0' High
Lat: 39.486778°
Long: 108.168697°

S89°55'12"W
2638.32' (Meas.)

SW Cor. Sec. 36,
1920 Brass Cap,
0.9' High
Lat: 39.481786°
Long: 108.178033°

S00°01'47"E
1813.28' (Meas.)

S00°02'15"E - 2639.41' (Meas.)

S00°02'37"E - 2634.46' (Meas.)

N00°05'12"W
1807.07' (Meas.)

SW Cor. Sec. 35,
1920 Brass Cap,
1.5' High
Lat: 39.481792°
Long: 108.196089°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486731°
Long: 108.196739°

N89°43'57"E - 2640.45' (Meas.)

N89°53'43"W - 2638.32' (Meas.)

1917 Brass Cap,
1.3' High
Lat: 39.486769°
Long: 108.187389°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486753°
Long: 108.215422°

N 1/4 Cor. Sec. 34,
True Position
Lat: 39.486769°
Long: 108.206092°

N 1/4 Cor. Sec. 34,
W.C.
1917 Brass Cap,
2.2' High
Lat: 39.486769°
Long: 108.206467°

105.60'
(G.L.O.)

S89°56'16"W
2633.86' (Meas.)

NW Cor. Sec. 34,
Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486753°
Long: 108.215422°

1807.07' (Meas.)

S00°04'15"W - 5287.69' (Meas.)

2322'

1694'

2402'

2285'

Top of Gas Interval

Bottom Hole

724'

768'

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486764°
Long: 108.178042°

S 1/4 Cor. Sec. 25,
1920 Brass Cap,
2.0' High
Lat: 39.486778°
Long: 108.168697°

S89°55'12"W
2638.32' (Meas.)

SW Cor. Sec. 36,
1920 Brass Cap,
0.9' High
Lat: 39.481786°
Long: 108.178033°

S00°01'47"E
1813.28' (Meas.)

S00°02'15"E - 2639.41' (Meas.)

S00°02'37"E - 2634.46' (Meas.)

N00°05'12"W
1807.07' (Meas.)

SW Cor. Sec. 35,
1920 Brass Cap,
1.5' High
Lat: 39.481792°
Long: 108.196089°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486731°
Long: 108.196739°

N89°43'57"E - 2640.45' (Meas.)

N89°53'43"W - 2638.32' (Meas.)

1917 Brass Cap,
1.3' High
Lat: 39.486769°
Long: 108.187389°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486753°
Long: 108.215422°

N 1/4 Cor. Sec. 34,
True Position
Lat: 39.486769°
Long: 108.206092°

N 1/4 Cor. Sec. 34,
W.C.
1917 Brass Cap,
2.2' High
Lat: 39.486769°
Long: 108.206467°

105.60'
(G.L.O.)

S89°56'16"W
2633.86' (Meas.)

NW Cor. Sec. 34,
Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486753°
Long: 108.215422°

1807.07' (Meas.)

S00°04'15"W - 5287.69' (Meas.)

LINE TABLE

LINE	DIRECTION	LENGTH
L1	N89°38'09"W	2640.48'
L2	S89°56'16"W	2528.26'

NOTE:

WELLBORE DATA PROVIDED BY
Caerus Oil & Gas LLC.

PDOP = 1.4

1000'

500'

0

1000'

NAD 83 (SURFACE LOCATION)	NAD 83 (TOP OF GAS INTERVAL)	NAD 83 (BOTTOM HOLE)
LATITUDE = 39°29'41.52" (39.494867)	LATITUDE = 39°29'19.95" (39.488876)	LATITUDE = 39°29'19.51" (39.488753)
LONGITUDE = 108°11'26.66" (108.190738)	LONGITUDE = 108°11'17.63" (108.188229)	LONGITUDE = 108°11'19.13" (108.188646)
NAD 27 (SURFACE LOCATION)	NAD 27 (TOP OF GAS INTERVAL)	NAD 27 (BOTTOM HOLE)
LATITUDE = 39°29'41.60" (39.494889)	LATITUDE = 39°29'20.03" (39.488898)	LATITUDE = 39°29'19.59" (39.488775)
LONGITUDE = 108°11'24.36" (108.190101)	LONGITUDE = 108°11'15.33" (108.187593)	LONGITUDE = 108°11'16.83" (108.188009)
UTM NAD 27 (ZONE 12)	UTM NAD 27 (ZONE 12)	UTM NAD 27 (ZONE 12)
N: 14354493.40 E: 2433180.89	N: 14352333.72 E: 2433956.86	N: 14352285.40 E: 2433840.61

CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED AND THE LOCATION AS SHOWN WAS STAKED ON THE GROUND FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
REGISTRATION NO. 19180
STATE OF COLORADO

08-30-18

BASIS OF BEARINGS

BEARINGS ARE A BASED ASSUMPTION THAT THE WEST LINE OF SECTION 26 BEARS S°04'15"W. MONUMENTS DESCRIBED HEREON.

BASIS OF ELEVATION

SPOT ELEVATION AT THE NORTHWEST CORNER OF SECTION 30, T5S, R95W, 6th P.M. TAKEN FROM THE FORKED GULCH QUADRANGLE, COLORADO, GARFIELD COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5966 FEET.

UELS, LLC

Corporate Office * 85 South 200 East
Vernal, UT 84078 * (435) 789-1017

Caerus Oil & Gas LLC

(AS-DRILLED) PUCKETT 25A-26-697
SE 1/4 NW 1/4, SECTION 26, T6S, R97W, 6th P.M.
GARFIELD COUNTY, COLORADO

SURVEYED BY	BART HUNTING, C.R.	10-02-17	SCALE
DRAWN BY	T.L.L.	08-21-18	1" = 1000'
AS-DRILLED WELL LOCATION PLAT			