

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved  
Budget Bureau No. 935  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

C-15260 AUG 2-1 1985

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

COLD OIL & GAS CONS. COMM

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Conoco Federal 21

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

So. McCallum/Pierre "B"

11. SEC., T., R., M., OR B.L. AND  
SURVEY OR AREA

Sec 21, T9N, R78W

12. COUNTY OR PARISH

Jackson

13. STATE

CO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Conoco Inc.

3. ADDRESS OF OPERATOR

907 North Poplar, Casper, WY 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

1850' FNL & 450' FEL, SE/NE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

8334' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

Conoco proposes to plug and abandon this well as follows:

1. POOH w/rods, pump & tubing.
2. Fill hole w/9.0 ppg mud.
3. Spot 25 sack class "G" cement plug @ approx 1120', cement plug will cover at least 100' over top of perforations.
4. Cut 5 1/2" and 8 5/8" casing 6' below ground level.
5. Spot a 30 sack cement plug from approx 100' to surface, including annular space between 5 1/2" and 8 5/8" casing.
6. Weld 1/4" x 8 5/8" plate on casing stub and install regulation dry hole marker.

A subsequent report will be submitted upon completion of abandonment. The surface will be reclaimed as soon as weather permits.



00222532

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE August 14, 1985

(This space for Federal or State office use)

APPROVED BY

TITLE

DIRECTOR

DATE

AUG 23 1985

CONDITIONS OF APPROVAL, IF ANY:

BLM - Craig (3)

COGCC (2)

SCE

File

\*See Instructions on Reverse Side