

OFFICE OF STATE OIL INSPECTOR
SUNDRY NOTICES AND REPORTS OF WELLS
LOCATED ON PRIVATE LANDS



2 approved Copies
Returned 8/7/51

185.2

(Indicate nature of data by checking below)

Notice of intention to drill X
Notice of intention to change plans
Notice of date for test of water shut-off
Report on result of test of water shut-off
Notice of intention to re-drill or repair well
Notice of intention to clean out well
Statement of shooting
Statement of perforating
Notice to pull or otherwise alter casing
Notice of intention to abandon well
Report of work done on well since previous report

Following is a (notice of intention to do work) (On land) August 3 19 51
(report of work done) (patented) described as follows:

COLORADO Logan YENTER POOL
State County Field
(1) ONE MAUDE M. KNOTSON "A" SW/4 Sec. 2 8N 54W
(Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)
The well is located 330 ft. (N) of North Line and 330 ft. (E) of
West Line of SW/4 Sec. 2 (S) (W)

The elevation above sea level is 4300' ft. G.L. (Est.)

Details of Plan of Work: (State names of and expected depths to objective sands:
Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
ing points, and all other important proposed work.)

To drill & test subject well to the "J" Sand of the Graneros Sand Series.
SURFACE CASING: 9-5/8" O.D. Armco Spiral Weld to be set at approximately 200' and cemented
with 150 sax. Cement to be circulated to ground surface.
PRODUCTION STRING CASING: 5 1/2" O.D., 15.5#, J-55 casing to be set thru the oil producing
section of the "J" Sand. Cement with 200 sax.
TESTING: 1. No coring planned. 2. DST "D" Sand if above minus 715'.
3. No DST planned for "J" Sand.
LOGGING: One run Schlumberger electric log from under surface casing point to T.D. Run Micro-
log on any indicated gas or oil zones.
DRIFT SURVEYS: At 50' intervals in surface hole and to a point 100' below surface casing, there-
after at 250' intervals. DRILLING TIME: Use Geolograph from 3500' to T.D.
SAMPLES: 5' intervals from 5000' to T.D. DEPTH MEASUREMENTS: S.L.M. of drill pipe at approx-
imately 4000' and prior to DST and at Total Depth. COMPLETION PROGRAM: Drill "J" Sand to a
minus T.D. of 870' or just into the water zone. Set & cement the oil string casing on bottom
(through the oil section) and perforate for production. EXPECTED SAMPLE TOPS: Niobrara 4240' -
Ft. Hays 4560' - Greenhorn 4820' - "D" Sand 5050' - "J" Sand 5155'

Approved: _____

Company The British American Oil Producing
Company

Address P. O. Box 620, Casper, Wyoming

By C. Wm. Evelyn, Jr.

Title Sup't., Northwestern District.

State Oil Inspector

Submit reports of proposed work, for approval, on this form in Duplicate.