T5S, R96W, 6th P.M.

LEGEND:

= 90° SYMBOL

= PROPOSED WELLHEAD.

= TOP OF GAS INTERVAL.

= TARGET BOTTOM HOLE.

= SECTION CORNERS LOCATED. (NAD 83)

1917 Brass Cap
2.5' High
Lat: 39.636808°
Long: 108.183536°

1917 Brass Cap
2.0' High
Lat: 39.636814°
Long: 108.174164°

1917 Brass Cap
2.3' High
Lat: 39.636808°
Long: 108.164797°

S89°50'59"W – 2640.58' (Meas.)

S89°55'26"W – 2638.66' (Meas.)

N00°09'25"W – 2634.15' (Meas.)

N00°11'59"W – 2633.21' (Meas.)

1917 Brass Cap
1.5' High, Wooden
Post, Pile of Stones
Lat: 39.629581°
Long: 108.183528°

1917 Brass Cap
2.5' High, Mound
of Stones
Lat: 39.629583°
Long: 108.164786°

9

See Detail "A"
@ Left

1303'

1242'

1261'

1239'

LINE TABLE		
LINE	DIRECTION	LENGTH
L1	S70°00'06"W	64.69'

1917 Brass Cap
1.7' High
Lat: 39.622329°
Long: 108.174151°

1917 Brass Cap
1.7' High,
Lat: 39.622329°
Long: 108.183516°

1917 Brass Cap
2.0' High, Pine Post
Lat: 39.622332°
Long: 108.164769°

Detail "A"
No Scale

Top of Gas
Interval

Target
Bottom Hole

L1

1242'

1303'

1239'

1261'

S89°53'09"W – 2638.95' (Meas.)

S89°51'22"W
2644.09' (Meas.)

1083'

N18°35'28"E
2475.93'

NPR 24C–9 596
Elev. Ungraded Ground = 8302.4'

2039'

N00°11'23"W – 2638.93' (Meas.)

N00°07'21"W – 2641.41' (Meas.)

BASIS OF BEARINGS

16

1917 Brass Cap
1.3' High
Lat: 39.615087°
Long: 108.183503°

1917 Brass Cap
1.7' High
Lat: 39.615083°
Long: 108.164769°

N00°14'18"W – 2638.32' (Meas.)

N00°07'05"W – 2638.68' (Meas.)

1917 Brass Cap
0.8' High, Steel Post
Lat: 39.607847°
Long: 108.183482°

S89°53'13"W – 2637.03' (Meas.)

1917 Brass Cap
2.5' High
Lat: 39.607847°
Long: 108.174126°

S89°55'00"W – 2637.39' (Meas.)

1917 Brass Cap
1.6' High, Rebar
Lat: 39.607842°
Long: 108.164770°

PDOP = 2.2

NAD 83 (SURFACE LOCATION)
LATITUDE = 39°37'09.68" (39.619356)
LONGITUDE = 108°10'19.21" (108.172003)
NAD 27 (SURFACE LOCATION)
LATITUDE = 39°37'09.77" (39.619380)
LONGITUDE = 108°10'16.92" (108.171366)
UTM NAD 27 (ZONE 12)
N: 14399997.55 E: 2437040.88

NAD 83 (TOP OF GAS INTERVAL)	NAD 83 (TARGET BOTTOM HOLE)
LATITUDE = 39°37'32.85" (39.625792)	LATITUDE = 39°37'32.63" (39.625731)
LONGITUDE = 108°10'09.06" (108.169184)	LONGITUDE = 108°10'09.84" (108.169400)
NAD 27 (TOP OF GAS INTERVAL)	**NAD 27 (TARGET BOTTOM HOLE)**
LATITUDE = 39°37'32.94" (39.625815)	LATITUDE = 39°37'32.72" (39.625755)
LONGITUDE = 108°10'06.77" (108.168548)	LONGITUDE = 108°10'07.55" (108.168763)
UTM NAD 27 (ZONE 12)	**UTM NAD 27 (ZONE 12)**
N: 14402366.29 E: 2437760.76	N: 14402342.39 E: 2437700.66

1000' 500' 0' 1000'

CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED AND LOCATION AS SHOWN WAS STAKED ON THE GROUND FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

COLORADO LICENSED PROFESSIONAL LAND SURVEYOR HAROLD D. NELSON MARSHALL 38130 PLS

REGISTERED LAND SURVEYOR
REGISTRATION NO. 38130
STATE OF COLORADO

09-05-18

BASIS OF BEARINGS

BEARINGS ARE A BASED ASSUMPTION THAT THE EAST LINE OF THE NORTHEAST 1/4 OF SECTION 16 BEARS N00°07'21"W. MONUMENTS DESCRIBED HEREON.

BASIS OF ELEVATION

BENCH MARK (H79) LOCATED IN THE NE 1/4 OF SECTION 35, T4S, R98W, 6th P.M. TAKEN FROM THE BULL FORK QUADRANGLE, COLORADO, 7.5 MINUTE SERIES (TOPO GRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 8535 FEET.

UINTAH ENGINEERING & LAND SURVEYING

UELS, LLC
Corporate Office * 85 South 200 East
Vernal, UT 84078 * (435) 789-1017

N

Caerus Oil & Gas LLC

NPR 24C-9 596
NW 1/4 NE 1/4, SECTION 16, T5S, R96W, 6th P.M.
GARFIELD COUNTY, COLORADO

SURVEYED BY	BART HUNTING, D.P.	03-20-18	SCALE
DRAWN BY	T.S.	08-14-18	1" = 1000'

WELL LOCATION PLAT