


075-06048

COLORADO OIL AND GAS CONSERVATION COMMISSION
SUNDRY NOTICES AND REPORTS OF WELLS



OIL & GAS
CONSERVATION COMMISSION

(Indicate nature of data by checking below)

304-10

Notice of intention to drill X
 Notice of intention to change plans _____
 Notice of date for test of water shut-off _____
 Report on result of test of water shut-off _____
 Notice of intention to re-drill or repair well _____
 Notice of intention to clean out well _____
 Statement of shooting _____
 Statement of perforating _____
 Notice to pull or otherwise alter casing _____
 Notice of intention to abandon well _____
 Report of work done on well since previous report _____

Following is a (notice of intention to do work) April 18 19 53
 (~~report of work done~~) (On land) (patented) described as follows:

Colorado Logan Yenter
 State County Field

6 Maude M. Knutson "A" Sec. 2 SW/4 8N 54W
 (Well No.) (Lease) (Sec. and $\frac{1}{4}$ Sec.) (Twp.) (Range) (Meridian)

The well is located 990 ft. (N) of North line and 990 ft. (E) of West line
 (S) (W)

The elevation above sea level is 4280 ft. K.B. (Est.)

Details of Plan of Work: (State names of and expected depths to objective sands:
 Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
 ing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Graneros Sand Series. Surface Casing:
 9-5/8" OD Armco Spiral Weld to be set at approximately 200' and cemented with 150 sax cement
 to be circulated to ground surface. Production String Casing: 5-1/2" OD 15.5# J-55 casing
 to be set through the oil producing section of the "J" Sand. Cement with 250 sax cement
 with 3% aquagel. Coring & Testing: No coring planned. No DST planned. Logging: One run
 Schlumberger electric log from under surface casing to T.D. Run Micro-log from -650' to T.D.
 Drift Surveys: At 50' intervals to 300', thereafter at 250' intervals. Samples: 10'
 samples from 4100' to 4900'. 5' samples from 4900' to T.D. Drilling Time: Use Geolograph
 from 4100'. Depth Measurements: S.L.M. of D.P. at approximately 4000', prior to any DST,
 and at T.D. Completion Program: Drill "J" Sand to -852'. Set and cement oil string casing
 on bottom and perforate -847' to -848' for production.

Approved: _____

APR 21 1953

Director

Company THE BRITISH-AMERICAN OIL PRODUCING CO.

Address 831 - 14th St., Denver 2, Colorado

By _____

Title District Superintendent

Submit reports of proposed work, for approval, on this form in Duplicate for patented lands and in Triplicate for school and state lands.