

































gyrodata

REPEAT PASS - Ran with 0 PSI

6 in / 100 ft

Database File 20190_06_16_extraction_of_cbl_vdl_70_150_to20190_06_16_extraction_of_cbl_vdl_70_150_rdb.db
Presentation Format Cased Hole Log
Charted by: Depth in Feet scaled 1:240



gyrodata

REPEAT PASS - Ran with 0 PSI

6 in / 100 ft

Database File d:\warrior\data\20190_06_16_extraction_of_cbl_vdl_70_150_to\20190_06_16_extraction_of_cbl_vdl_70_150_rdb.db
Dataset Creation Wed Aug 15 07:27:37 2018

Calibration Report

Gamma Ray Calibration Report

Serial Number	GSXCC-01
Tool Model	2 3/4" TNG
Calibration Date	07-AUG-18 07:00 2018
Calibrator Value	104.0 GAPI
Background Reading	30.9 cps
Background Counting	60 sec
Sensitivity	0.2535 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number	SPDCS-01
Tool Model	2 3/4" SGL Analog
Calibration Casing Diameter	4.500 in
Calibration Depth	544.560 ft

Master Calibration, performed Sun Aug 12 11:27:32 2018

	Raw (c)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.008	0.908	0.000	71.921	79.212	-0.662
CAL	0.000	0.503				
5'	0.010	1.166	0.000	71.921	61.637	-0.594
SUM						
0.1	0.017	0.905	0.000	72.000	81.008	-1.327
0.2	0.015	0.907	0.000	72.000	80.829	-1.202
0.3	0.015	0.907	0.000	72.000	79.380	-1.104
0.4	0.015	0.907	0.000	72.000	79.380	-1.104
0.5	0.015	0.907	0.000	72.000	79.380	-1.104
0.6	0.016	0.913	0.000	72.000	79.212	-1.151
0.8	0.018	0.913	0.000	72.000	64.296	-1.305
1.0	0.018	0.913	0.000	72.000	64.296	-1.305

Internal Reference Calibration, performed Fri Aug 05 15:12:20 017

	Raw (c)		Calibrated (c)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.000	0.503	1.000	0.000

Arr Zero Calibration, performed Fri Aug 26 16:13:11 2017

	Raw (c)		Calibrated (c)		Results	
	Zero		Zero		Offset	
3'	0.000		0.000		0.000	
CAL	0.000		0.000		0.000	
SUM						
0.1	0.000		0.000		0.000	
0.2	0.000		0.000		0.000	
0.3	0.000		0.000		0.000	
0.4	0.000		0.000		0.000	
0.5	0.000		0.000		0.000	
0.6	0.000		0.000		0.000	

Temperature Calibration Report

Serial Number	SPDCS-01
Tool Model	2 3/4" SGL Analog
Performed	Fri Aug 17 07:30 2018
	Reference
	Reading
Low Reference	0.00 degF 0.00 ohms
High Reference	0.00 degF 0.00 ohms
Offset	0.00
Gain	0.00
Delta Spacing	

Sensor	Offset (ft)	Schematic	Description	Length (ft) O.D. (in)	Weight (lb)
			Cablehead TlacCon/Cpod	1.03 1.44	3.60
CCL	13.50		CCL_Log-2 3/4" TeCo (PSNT-03)	1.83 2.75	33.00
TEMP	16.05		Antelope Overbody	1.20 2.75	
WVF35	8.76		RBTR-2 3/4" RIB Analog (VPCS-01)	9.13 2.75	102.00
WVF32	8.76				
WVF31	8.76				
WVF33	8.76				
WVF23	8.76				
WVF22	8.76				
WVF21	8.76				
WVF13	7.31				
WVF11	7.31				
WVFSYNC	3.68		Antelope Overbody	1.25 2.75	
WVFTEMP	3.68				
WVFCAL	3.68		CPL_Log-2 3/4" TeCo (SWHD-02)	3.68 2.75	47.00
CR	1.04				
LOCTOR	0.00				
LOCTOR	0.00				
PMON	0.00				

Saved: 20190_06_16_extraction_of_cbl_vdl_70_150_rdb.db :: field\warrior\1case3
Total length: 10.42 ft
Total weight: 0.00 lb
OD: 2.75 in