

Click here to reset the form

FORM
21
Rev 9/14

State of Colorado
Oil and Gas Conservation Commission



1120 Lincoln Street, Suite 801, Denver, Colorado 80203 (303)-894-2100 Fax: (303)-894-2109

MECHANICAL INTEGRITY TEST

1. Duration of the pressure test must be a minimum of 15 minutes.
2. An original pressure chart must accompany this report if this test was not witnessed by a OGCC representative. Injection wells tests must be witnessed by an OGCC representative.
3. For production wells, test pressures must be at a minimum of 300 psig.
4. New injection wells must be tested to maximum requested injection pressure.
5. For injection wells, test pressures must be at least 300 psig or average injection pressure, whichever is greater.
6. A minimum 300 psi differential pressure must be maintained between the tubing and tubing/casing annulus pressure.
7. Do not use this form if submitting under provisions of Rule 326.a.(1) B. or C.
8. OGCC notification must be provided 10 days prior to the test via Form 42.
9. Packers or bridge plugs, etc., must be set within 100 feet of the perforated interval to be considered a valid test.

OGCC Operator Number: 10539	Contact Name and Telephone Norm Schwalm
Name of Operator: Utah Gas Corp.	No: (303) 808-5049
Address: 1125 Escalante Drive	Email: nschwalm@utahgascorp.com
City: Rangely State: CO Zip: 81648	
API Number: 05-077-08814 OGCC Facility ID Number: 273740	
Well/Facility Name: Federal BW2B Well/Facility Number: 2B	
Location QtrQtr: NWNW Section: 1 Township: 9S Range: 104W Meridian: 6PM	

FOR OGCC USE ONLY

Document Number:

Date Received:

Complete the
Attachment Checklist

	Oper	OGCC
Pressure Chart		
Cement Bond Log		
Tracer Survey		
Temperature Survey		
Inspection Number	680403	776

☒ SHUT-IN PRODUCTION WELL

☐ INJECTION WELL

Last MIT Date: 10/08/2013

Test Type:

☒ Test to Maintain SI/TA status

☒ 5-year UIC

☐ Reset Packer

☐ Verification of Repairs

☐ Annual UIC Test

Describe Repairs or Other Well Activities:

Wellbore Data at Time of Test

Injection/Producing Zone(s) Entrada	Perforated Interval: 3066 - 3086	Open Hole Interval:
--	-------------------------------------	---------------------

Casing Test Use when perforations or open hole is isolated by bridge plug or cement plug; use if cased-hole only with plug back total depth.
Bridge Plug or Cement Plug Depth 3020

Tubing Casing/Annulus Test

Tubing Size: " 2 3/8	Tubing Depth: 2984'	Top Packer Depth:	Multiple Packers? <input type="checkbox"/> Yes <input type="checkbox"/> No
----------------------	---------------------	-------------------	---

Test Data

Test Date 9/24/18	Well Status During Test SI	Casing Pressure Before Test 0	Initial Tubing Pressure	Final Tubing Pressure
Casing Pressure Start Test 408	Casing Pressure - 5 Min. 406	Casing Pressure - 10 Min. 406	Casing Pressure Final Test 405	Pressure Loss or Gain During Test -.3
Test Witnessed by State Representative? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		OGCC Field Representative (Print Name): Chuck Browning		

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct, and complete.

Print Name: Norm Schwalm

Signed: Norm Schwalm Title: Petroleum Engineer

Date: 9/24/18

OGCC Approval: [Signature] Title: NW Insp

Date: 9/24/18

Conditions of Approval, if any: