

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400967938

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 69175

2. Name of Operator: PDC ENERGY INC

3. Address: 1775 SHERMAN STREET - STE 3000

City: DENVER State: CO Zip: 80203

4. Contact Name: Ally Ota

Phone: (303) 860-5800

Fax: (303) 831-3988

Email: Alexandria.Ota@pdce.com

5. API Number 05-123-40716-00

7. Well Name: Peschel

8. Location: QtrQtr: SWSW Section: 20 Township: 4N Range: 65W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 20H-302

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 12/09/2015 End Date: 12/17/2015 Date of First Production this formation: 01/01/2016
Perforations Top: 7705 Bottom: 11521 No. Holes: 708 Hole size: 42/100

Provide a brief summary of the formation treatment:

Open Hole: ☐

20 Stage Plug and Perf, Perf'd from 7,705'-11,216', 3 Toe Sleeve from 11,428'-11,518'

Total Fluid: 70,708 bbls

Gel Fluid: 50,544 bbls

Slickwater Fluid: 19,170 bbls

15% HCl Acid: 994 bbls

Total Proppant: 2,942,300 lbs

Silica Proppant: 2,942,300 lbs

Method for determining flowback: measuring flowback tank volumes.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 70708

Max pressure during treatment (psi): 4829

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.97

Total acid used in treatment (bbl): 994

Number of staged intervals: 20

Recycled water used in treatment (bbl):

Flowback volume recovered (bbl): 3162

Fresh water used in treatment (bbl): 69714

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 2942300

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 01/06/2016 Hours: 24 Bbl oil: 199 Mcf Gas: 1651 Bbl H2O: 276
Calculated 24 hour rate: Bbl oil: 199 Mcf Gas: 1651 Bbl H2O: 276 GOR: 8296
Test Method: Flowing Casing PSI: 3029 Tubing PSI: 2485 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1230 API Gravity Oil: 61
Tubing Size: 2 + 3/8 Tubing Setting Depth: 7271 Tbg setting date: 12/31/2015 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Cassie Gonzalez

Title: Regulatory Technician Date: Email: Cassie.Gonzalez@pdce.com

Attachment Check List

Att Doc Num Name

Total Attach: 0 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)