Operator	*Fremont Oil and Gas Corporation*
Operator No.	10412
Well NO.	JW Powell #23-35
Lease Name	
API No.	TBD
County	Fremont
State	Colorado
Spud Date	TBD
AFE #	

QtrQtr	NESW
Section	35
Township	19S
Range	70W
Meridian	6
FSL	1325'
FWL	2379'

Well Coordinates	North	East
Surface	1187825.12202900'	3088682.91219700'
Bottom		

CO-SP NAD 83

Well Elevation Reference	
Elevation (ft)	
Kelly Bushing (ft)	
Rig Floor (ft)	
Ground Level (ft)	

Casing Type	Formation	Tops	Hole Size (")	Casign Diam (")	TVD (')	MD (')	Casing Specs		Additional Comments: Cement, Pressure Test, etc	
				12.715						
Conductor			14.75	13.375	40.00	40.00				
	Vermejo			ID						
				10.050					Hammer Bit	
	Trinidad & Transition	834		ID (drft)				Prv csg - cplg (inches)	Casing Bouyed Wtg (Lbs)	33,339
				9.894				0.965	Casing String Wtg (Lbs)	38,475
				OD				Cplg OD 11.75	Annu. Capa (Bbls/ft)	0.037
Surface			12.375	10.750	950	950	40.5 #/ft		Annu. Volume (Bbls)	35
	Cone-in-Cone	2010							PDC Bit	
	Tee Pee Butte	2750		ID					Intermediate Casing will require bottom cementing.	
				6.456					Reverse Air Drilling	
	Rusty	3340		ID (drft)				Prv csg - cplg (inches)	Casing Bouyed Wtg (Lbs)	84,051
				6.331				2.238	Casing String Wtg (Lbs)	97,000
	Sharon Springs	4722		OD				Cplg OD 7.656	Annu. Capa (Bbls/ft)	0.023
Intermediate			8.500	7.000	4850	4850	20 #/ft		Annu. Volume (Bbls)	23
	Niobrara	5134							Drilling Fluid Capability in Surface	
	Niobrara A	TBD								
	Niobrara B	TBD								
	Niobrara D	TBD								
	Ft. Hayes	5620								
	Codell	5670								
	Greenhorn	6106								
	Lytle	6268		ID						
				3.826						
	Morrison	6302		ID (drft)				Prv csg - cplg (inches)	Casing Bouyed Wtg (Lbs)	85,048
				4.407				1.331	Casing String Wtg (Lbs)	98,150
				OD				Cplg OD 5	Annu. Capa (Bbls/ft)	0.017
Production			6.125	4.500	6500	6500	15.1 #/ft		Annu. Volume (Bbls)	35.2
Casing Type	Formation	Top	Hole Size (")	Casign Diam (")	TVD (')	MD (')	Casing Specs		Additional Comments: Cement, Pressure Test, etc	