

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DEC - 3 1998

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

RIATA ENERGY, INC.

3. Address and Telephone No.

P.O. BOX 10209 AMARILLO, TX 79116-0209 (806) 352-2936

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

3' FSL & 808' FEL
SE SE SEC 23, T3S - R99W

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

FEDERAL 399 #23-1

9. API Well No.

05-103-9914

10. Field and Pool, or Exploratory Area

GREEN RIVER

11. County or Parish, State

RIO BLANCO, CO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MI & RU Himes Drilling Rig #8
Drill 12-1/4" surface hole to 50'.
Run 50' 8-5/8" csg. Cement to surface w/ 16 Sxs Class "G" cement.
Drill 7-7/8" hole, 50' - 555'. Run 550' 5-1/2" csg, 10.5#, Rge 3.
BJ Cement 5-1/2" Csg - 36 Sxs Class "C" cement - 70 Sxs Class "G" cement, 150% Excess
Circulate 10 Bbls good cement
Drill 4-7/8" hole, 550' - 820'. TD @ 820'
RD & MO Himes Drilling
Well left w/ 5-1/2", 3000# Frac Valve; 5-1/2" x 2" Swedge & 2", 2000# Valve
SWI.



14. I hereby certify that the foregoing is true and correct

Signed

Title Production Manager

Date 11/13/98

(This space for Federal or State office use)

Approved by

Title

NWA E

Date

12-10-98

Conditions of approval, if any:

SUBMIT COMPLETION REPORT (FORM 5) BY 2-1-99