



3073672

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED DEC - 3 1998

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

RIATA ENERGY, INC.

3. Address and Telephone No.

P.O. BOX 10209 AMARILLO, TX 79116-0209 (806) 352-2936

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

3' FSL & 808' FEL SE SE SEC 23, T3S - R99W

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. FEDERAL 399 #23-1

9. API Well No. 05-103-9914

10. Field and Pool, or Exploratory Area GREEN RIVER

11. County or Parish, State RIO BLANCO, CO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- XX Notice of Intent
Subsequent Report
Final Abandonment Notice

- Abandonment
Recompletion
Plugging Back
Casing Repair
Altering Casing
Other

- Change of Plans
New Construction
Non-Routine Fracturing
Water Shut-Off
Conversion to Injection
Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

RIATA ENERGY, INC. provides notice of change in plans as indicated in Sundry Notice, dated 10/5/98 as follows: Request to change csg program to better protect the fresh water zones. This will allow the testing of the Green River for commercial gas & less water. Set 50' of 7-7/8" Cement to surface. Drill 7 1/4" hole to 550'. Set 550' of 5-1/2", 15.5#, J-55 csg Cement to surface. Drill out from 5-1/2" to 800'+. Complete open-hole.



RECEIVED DOBBLM CO 017 HECKER, CO 81641 98OCT 19 PM 1:27

14. I hereby certify that the foregoing is true and correct

Signed Susan J. Piessner

Title Regulatory Agent/ Eng. Tech

Date 10/13/98

(This space for Federal or State office use)

Approved by Brad Loney

Title Petroleum Engineer

Date 10/26/98