



SRC ENERGY

Operator: SRC Energy
Well Name: Mossberg J 31-27
Legal: SESE, Section 30, Township 5N, Range 66W
Location: Weld County, CO
API: 05-123-28058
Surface: 8.625" 24# @ 852' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,496' **Hole Size:** 7.875" **TOC:** 1273' (CBL)
Perforations: 7,041' – 7,180' (Niobrara), 7,340'–7,350' (Codell)
TD: 7,496'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 6,970'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 25 sx on top of existing CIBP (330' plug)
8. Cut 4.5" casing at 1000' and POOH
9. TIH to 1050' and pump stub plug (0' – 1050')
 - a. 325 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete