

Operator:	SRC Energy				
Well Name:	BOOTH #25-15				
Legal:	SWNE 25 5N 67W				
Location:	Weld County, CO				
API:	05-123-28106				
Surface:	8.625" 24# @	1031'	Hole Size: 12.25"	TOC: Surface	
Production:	4.5" 11.6# @	7665'	Hole Size: 7.875"	TOC: 530' (CBL)	
Perforations:	7204-7426 NIOBRARA		7528-7546 CODELL		
TD:	7687'				

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP on tubing, set at 7129'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 35 sx on top of existing CIBP (460' plug)
8. TIH w/4-1/2" 11.6# CIBP on tubing, set at 1131'
9. Set 15 sx on top of existing CIBP (200' plug)
10. Shoot holes in 4.5" casing @ 500'
11. Circulate 170 SXS to surface
 - a. pump 170 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Wait 4 hours and tag plug
12. RDMO WO unit
13. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
14. Weld on cap with ID plate, inscribed with well location, and identity
15. Backfill, clean location
16. P&A complete