

1) Provide 24 hour notice of MIRU to Ed Binkley at 970-506-9834 or e-mail at ed.binkley@state.co.us 2) Comply with Rule 317.1 and provide cement coverage from TD to a minimum of 200' above Niobrara and from 200' below Shannon to 200' above Sussex. Verify coverage with cement bond log.

LOCATION: SW1/4 OF NW1/4 OF SEC. 28, T.2N., R.67W. (1881 NSL, 515 WSL)

Ground Elevation: 5026

Number of Acres: 0

AQUIFER	ELEVATION		NET SAND	DEPTH TO		ANNUAL APPROP A-F	STATUS
	BOT.	TOP		BOT.	TOP		
UPPER DAWSON	----	----	----	----	----	----	----
LOWER DAWSON	----	----	----	----	----	----	----
DENVER	----	----	----	----	----	----	----
UPPER ARAPAHOE	----	----	----	----	----	----	----
LOWER ARAPAHOE	----	----	----	----	----	----	----
LARAMIE-FOX HILLS	4422	4694	193.1	604	332	0.00	NT

note: E indicates location is at aquifer boundary and values
may be more approximate.



Well name and number:

Heisman V 28-5

SWNW-528-T2N-R67W

Survey Plat Check list

number	Item	
	8-1/2" x 11" scaled drawing of the entire section	
1	Dimensions on adjacent exterior section lines sufficient to completely describe the quarter section containing the proposed well shall be indicated	OK
1a	If dimensions are not field measured, state how the dimensions were determined	OK
2	For directional drilling into an adjacent section, that section shall also be shown on the location plat and dimensions on exterior section lines sufficient to completely describe the quarter section containing the proposed productive interval and bottom hole location shall be indicated.	N/A
3	For irregular, partial or truncated sections, dimensions will be furnished to completely describe the entire section containing the proposed well.	N/A
4	The field measured distances from the nearer north/south and nearer east/west section lines shall be measured at ninety (90) degrees from said section lines to the well location and referenced on the plat.	OK
4.1*	For unsurveyed land grants and other areas where an official public land survey system does not exist the well locations shall be spotted as footages on a protracted section plat using Global Positioning System (GPS) technology and also reported as latitude and longitude in accordance with the requirements set forth below: in 4A, 4B, 4C	N/A
4A*	All GPS data reported to the Commission shall be differentially corrected using base station data or other correction sources. The base station or other correction source shall be identified and reported with the coordinate values.	
4B*	Coordinates shall be reported as latitude and longitude in decimal degrees to an accuracy of at least five (5) decimal places (e.g.; latitude 37.12345 N, longitude 104.45632 W).	
4C*	All data shall be referenced to the North American Datum (NAD) of 1927.	✓
4D	The date of the survey shall be reported.	OK
5	A map legend	
6	A North Arrow	
7	A scale expressed as an equivalent (e.g. 1" = 1000').	
8	A bar scale.	
9	The ground elevation.	
10	The basis of the elevation (how it was calculated or its source).	
11	The basis of bearing or interior angles used.	
12	Complete description of monuments and/or collateral evidence found; all aliquot corners used shall be described.	
13	The legal land description by section, township, range, principal meridian, baseline and county.	
14	Operator name	
15	Well name and number	✓
16	Date of completion of scaled drawing	OK
17a	All visible improvements within two hundred (200) feet of a wellhead (or, in a high density area within four hundred (400) feet of a wellhead) shall be physically tied in and plotted on the well location plat or on an addendum, with a horizontal distance and approximate bearing from the well location.	N/A
17b	Visible improvements shall include, but not be limited to, all buildings, publicly maintained roads and trails, major above-ground utility lines, railroads, pipelines, mines, oil wells, gas wells, injection wells, water wells, visible plugged wells, sewers with manholes, standing bodies of water, and natural channels including permanent canals and ditches through which water flows.	N/A
17c	If there are no visible improvements within two hundred (200) feet of a wellhead (or in a high density area within four hundred (400) feet of a wellhead), it shall be so noted on the Permit-to-Drill, Form 2.	OK
18	Surface use shall be described within the two hundred (200) foot radius of a wellhead (or in a high density area within the four hundred (400) foot radius of a wellhead).	OK

* Only required for unsurveyed land grants and other areas where an official public land survey system does not exist.

The survey plat you submitted with your permit was found to be in non-compliance with COGCC rule 303c. See above checklist. If a survey plat is not in compliance with rule 303c the operator will be notified and the permit will be placed on hold until an adequate replacement is supplied to the COGCC.

good