

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400813099

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 69175

2. Name of Operator: PDC ENERGY INC

3. Address: 1775 SHERMAN STREET - STE 3000

City: DENVER State: CO Zip: 80203

4. Contact Name: Ally Ota

Phone: (303) 860-5800

Fax: (303) 831-3988

Email: Alexandria.Ota@pdce.com

5. API Number 05-123-39757-00

7. Well Name: Suden

8. Location: QtrQtr: NENE Section: 34 Township: 5N Range: 64W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 34U-243

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 03/16/2015 End Date: 03/16/2015 Date of First Production this formation: 04/02/2015
Perforations Top: 7209 Bottom: 11118 No. Holes: Hole size:

Provide a brief summary of the formation treatment:

Open Hole: ☒

20 Stage Sliding Sleeve, Swell Packer set at 7209'.
Total Fluid: 69,289 bbls
Gel Fluid: 57,967 bbls
Slickwater Fluid: 11,322 bbls
Total Proppant: 4,395,520 lbs
Silica Proppant: 4,395,520 lbs
Method for determining flowback: measuring flowback tank volumes.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 69289

Max pressure during treatment (psi): 3997

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.95

Total acid used in treatment (bbl):

Number of staged intervals: 20

Recycled water used in treatment (bbl):

Flowback volume recovered (bbl): 7620

Fresh water used in treatment (bbl): 69289

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 4395520

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 04/08/2015 Hours: 24 Bbl oil: 253 Mcf Gas: 722 Bbl H2O: 382
Calculated 24 hour rate: Bbl oil: 253 Mcf Gas: 722 Bbl H2O: 382 GOR: 2854
Test Method: Flowing Casing PSI: 2530 Tubing PSI: 1526 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1305 API Gravity Oil: 52
Tubing Size: 2 + 3/8 Tubing Setting Depth: 6797 Tbg setting date: 04/01/2015 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

** Bridge Plug Depth:

** Sacks cement on top:

** Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Cassie Gonzalez

Title: Regulatory Technician Date: Email: Cassie.Gonzalez@pdce.com

Attachment Check List

Att Doc Num Name

Total Attach: 0 Files

General Comments

User Group

Comment

Comment Date

--

--

Stamp Upon
Approval

Total: 0 comment(s)