Schlumberger
Canada Limited
Services

DUAL INDUCTION - SFL
GAMMA RAY - SP

RUN 1
26-JUL-84

CASING
BIT SIZE
TYPE FLUID
DENSITY
VISCOSITY
PH
FLUID LOSS
SOURCE OF SAMPLE
RM @ MEAS TEMP
RMF @ MEAS TEMP
RMC @ MEAS TEMP
SOURCE RMF
SOURCE RMC
RM @ BHT
TIME CIRC
MAX REC TEMP
EQUIP #
LOCATION
RECORDED BY
WITNESSED BY

This data is the property of Schlumberger and is delivered subject to the terms and conditions of the agreement pursuant to which it is furnished. Any reproduction, redistribution or retransmission in any form or by any means, electronic or mechanical, now known or hereafter invented, including but not limited to facsimile transmission, photocopying, photographing and recording, in whole or in part, is forbidden unless prior written permission is obtained from Schlumberger. Any user hereof agrees that Schlumberger shall not be liable for any loss, cost, damage or expense that may be incurred or sustained by anyone resulting from any interpretation made by any of its officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current price schedule.

Trademark

LDS-N-NGT COMPILATED

Calibration Report

Company/Client: ESSO RE
Well/Field/Location: Well No. 30-19-49-5 W.M.

Log Type: DUAL INDUCTION-SFL

DUAL INDUCTION

Mud Resistivity (Rm) at Measured Temperature (MT): 0.17 ohmm @ 68 deg F
Source of Rm: Recirculated
Rm @ MT: 0.17 ohmm @ 68 deg F
Mud Filtrate Resistivity (Rmf) at MT: 0.15 ohmm @ 68 deg F
Source of Rmf: Recirculated
Mud Cake Resistivity (Rmc) at MT: 0.19 ohmm @ 68 deg F
Source of Rmc: Recirculated
Rm at BHT: 0.08 ohmm @ 180 deg F
Time Since Circulation: 4 hrs
Max. Recorded Temperature: 180 deg F
Equipment Number: 1
Location: Edmonton
Recorded By: R. Hall
Witnessed By: Mr. Hall

	Tool Value	Borehole Value	Scale
SHORT NORMAL	0.17 ohmm	0.17 ohmm	
Deflection	2.5 div	2.5 div	
Calculation	0.17 x 2.5 = 0.425		
PRIMARY			
Deflection	2.5 div		10 ohmm
Calculation	0.425 x 2.5 = 1.06		1 ohmm
MICRO GUARD			
Deflection	2.5 div		10 ohmm
Calculation	0.425 x 2.5 = 1.06		1 ohmm
AFTER GUARD			
Deflection	2.5 div		10 ohmm
Calculation	0.425 x 2.5 = 1.06		1 ohmm

Control Room Log Validation Report

Company/Client: ESSO RE
Well/Field/Location: Well No. 30-19-49-5 W.M.

Log Type: DUAL INDUCTION-SFL

Tool Number	1		
Tool Type	DIL-SFL		
Logging Direction	Down		
Depth Interval	1270 ft to 1270 ft		
	0 feet/min	0 feet/min	
Speed Error	0 - 10%	0 - 10%	0%
Depth Error	0 - 0.5%	0 - 0.5%	0%
Tension Error	0 - 10%	0 - 10%	0%
Time	12:00	12:00 hrs	
Date	26-JUL-84	26-JUL-84	

Company/Client: ESSO RE
Well/Field/Location: Well No. 30-19-49-5 W.M.
Measured Depth: 1270 ft
Log Type: DUAL INDUCTION-SFL

Schlumberger Canada Limited Services
Edmonton, Alberta

Schlumberger Canada Limited Services
Edmonton, Alberta

Schlumberger Canada Limited Services
Edmonton, Alberta