



SRC ENERGY

Operator: SRC Energy
Well Name: LHI 14-44
Legal: SESE, Section 14, Township 4N, Range 67W
Location: Weld County, CO
API: 05-123-19811
Surface: 8.625" 24# @ 388' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,461' **Hole Size:** 7.875" **TOC:** 130' (Reported)
Perforations: 7,291' – 7,311' (Codell)
TD: 7,471'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 7,216'
6. Pressure test casing to 500 psi for 15 minutes (potential hole between 6732-6927')
7. Run CBL from 7,216' to surface
8. Set 52 sx on top of existing CIBP (cover 440' above Niobrara top)
9. TIH to 800' and pump surface plug (0' – 800')
 - a. 60 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete