



SRC ENERGY

Operator: SRC Energy
Well Name: Warren McMillan Unit #2
Legal: NWSW, Section 19, Township 4N65W, Range 6PM
Location: Weld County, CO
API: 05-123-09453
Surface: 8.625" 24# @ 421' MD **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 10.5# @ 4606' MD **Hole Size:** 8.625" **TOC:** 3,634' (Calculated)
Perforations: 4466'-4506' (Sussex)
TD: 4606' MD

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 4,391' MD.
6. Set 16 sxs on top of CIBP (200' above Sussex)
7. RIH to 1,800' and perforate casing
8. TIH w/ 4-1/2" 11.6# CICR, set at 1,700'
 - a. Squeeze perfs w/ 80 sx (400' annulus plug)
 - b. Release from CICR and set 8 sx on top (100' plug)
9. Cut 4.5" @ 900' MD, and POOH
10. TIH to 950' and pump stub plug (0' – 950')
 - a. 296 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&R complete