



SRC ENERGY

Operator: SRC Energy
Well Name: Oster-Molander #1
Legal: NWSE, Section 30, Township 4N, Range 65W
Location: Weld County, CO
API: 05-123-09424
Surface: 8.625" 24# @ 429' MD **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 4670' MD **Hole Size:** 7.875" **TOC:** 3665' (Calc)
Perforations: 4534'-4552' (Sussex)
TD: 4670' MD

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. RIH with CBL and gyro
6. TIH w/ 4-1/2" 11.6# CIBP, set at 4459' MD.
7. Pressure test casing to 500 psi for 15 minutes
8. Set 23 sx on top of existing CIBP (cover 300' above Sussex)
9. TIH to 2500' MD and perforate
10. Set CICR @ 2400' MD, pump 60 sx through CICR
11. Set 8 sx on CICR
12. Cut 4.5" @ 1000' MD, and POOH
13. TIH to 1050' and pump stub plug (0' – 1050')
 - a. 317 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
14. RDMO WO unit
15. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
16. Weld on cap with ID plate, inscribed with well location, and identity
17. Backfill, clean location
18. P&A complete