

Operator:	SRC Energy		
Well Name:	WERNING #4-2		
Legal:	NWNW 2 4N 66W		
Location:	Weld County, CO		
API:	05-123-19836		
Surface:	8.625" 24# @ 437'	Hole Size: 12.25"	TOC: Surface
Production:	4.5" 11.6# @ 7360'	Hole Size: 7.875"	TOC: 6290' (CBL)
Perforations:	7177-7189 CODELL		
TD:	7365		

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP on tubing, set at 7102'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 35 sx on top of existing CIBP (450' plug)
8. TIH w/perf gun to 4403' and perforate casing
9. TIH w/ 4-1/2" 11.6# CICR, set at 4203'
 - a. pump 84 sks of 15.8# class G neat 1.15 cu./ft. yield cement - (345' Annular Plug)
 - b. Release off of CICR and pump 9 sx (110' casing plug)
10. Cut 4.5" casing @ 800'
11. TIH with tubing to 850' and pump stub plug from 0 - 850'
 - a. pump 264 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
12. RDMO WO unit
13. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
14. Weld on cap with ID plate, inscribed with well location, and identity
15. Backfill, clean location
16. P&A complete