



Partner Summary Report

Date: 3/5/2019

Report #: 2

Well Name: SPIKE STATE D10-23

DOL:

Spud Date: 6/28/2005

Well Header

Well Name SPIKE STATE D10-23	API 05-123-22932	County/Parish WELD	State/Province COLORADO	Total Depth All (TVD) (ftKB)	Current PBTD (ftKB) ORIGINAL HOLE - 7,515.0		
Spud Date 6/28/2005	TD Date		Rig Release Date 7/3/2005		First Gas Sales		
Actual Latitude (°) 40.23631616	Actual Longitude (°) -104.53224373	Quarter 3 SE	Quarter 4 SE	Section 10	Township 3	Township N/S Dir N	Range E/W Dir W

Job: ABANDON , Job Start Date: 2/26/2019 14:00

Objective P&A	AFE Number
------------------	------------

Report Start Date 3/5/2019 12:30	Report End Date 3/5/2019 15:30	Operations Summary WP 1000-1000 SCP-10 BULLS EYE LAID THE BLOWBACK LINE THE NIGHT BEFORE. HAVE RAIN FOR RENT SPOT THE OPEN TOP TANK. HAVE ATLAS DELIVER A TOILET. SPN ARRIVED. NPT WATER TRUCK ARRIVED. GO OVER THE JOB AND JSA WITH SPN, NPT AND BULLS EYE. FINISH HOOKING UP THE HARD LINE. CHECK WELL PRESSURE. OPEN THE TUBING TO THE LINE AND PRESSURE TEST . BLOW THE WELL DOWN. WATCH THE CASING PRESSURE TO SEE WE HAD A PRESSURE DIFFERENTIAL. PRESSURE TEST LINES TO 1500 PSI. PUMP DOWN THE TUBING AND ROLL THE OIL AND GAS OUT. 110 BBLS TO GET CIRCULATION. PUMP 200 BBLS OF H2O. MIX AND PUMP 7.1 BBLS (34.6 SKS) OF G NEAT. DISPLACE WITH 25 BBLS TO BALANCE THE PLUG AT6501'-6907' SHUT DOWN. BOTH SIDES ON A SLIGHT VAC. BLOW THE LINE CLEAN. RD THE FLOW BACK LINE. SHUT THE WELL IN. MO. CEMENT PLUG 6501'-6907' 34.6 SKS 7.1 BBLS
-------------------------------------	-----------------------------------	---