



Partner Summary Report

Date: 3/19/2019

Report #: 1

DOL:

Well Name: WARDLAW 16-28

Spud Date: 11/26/2003

Well Header

Well Name WARDLAW 16-28	API 05-123-21812	County/Parish WELD	State/Province COLORADO	Total Depth All (TVD) (ftKB)	Current PBTD (ftKB) ORIGINAL HOLE - 6,981.0		
Spud Date 11/26/2003	TD Date 11/30/2003	Rig Release Date 12/1/2003	First Gas Sales				
Actual Latitude (°) 40.45134000	Actual Longitude (°) -104.54876000	Quarter 3 SE	Quarter 4 SE	Section 28	Township 6	Township N/S Dir N	Range E/W Dir W

Job: ABANDON , Job Start Date: 3/19/2019 12:00

Objective P&A	AFE Number
------------------	------------

Report Start Date 3/19/2019 12:00	Report End Date 3/19/2019 15:00	Operations Summary WP 1320/1320 SCP-0 BULLS EYE LAID THE BLOWBACK LINE THE NIGHT BEFORE. HAVE RAIN FOR RENT SPOT THE OPEN TOP TANK. HAVE RECK FLYERS DELIVER A TOILET. SPN ARRIVED. NPT WATER TRUCK ARRIVED. GO OVER THE JOB AND JSA WITH SPN, NPT AND BULLS EYE. FINISH HOOKING UP THE HARD LINE. CHECK WELL PRESSURE. OPEN THE TUBING TO THE LINE AND PRESSURE TEST. BLOW THE CASING DOWN 300 TUBING AT 600 PSI. SEE WE HAD A PRESSURE DIFFERENTIAL. PRESSURE TEST LINES TO 1500 PSI. PUMP DOWN THE TUBING AND ROLL THE OIL AND GAS OUT. 120 BBLS TO GET CIRCULATION. PUMP 180 BBLS OF H2O. MIX AND PUMP 7.5 BBLS (36.5 SKS) OF G NEAT. DISPLACE WITH 24.87 BBLS TO BALANCE THE PLUG CEMENT PLUG AT 6860'-6426' SHUT DOWN. SHUT THE WELL IN. BLOW THE LINE CLEAN. RD THE FLOW BACK LINE.. MO. CEMENT PLUG 6860'-6426' 36.5 SKS/ 7.5 BBLS
--------------------------------------	------------------------------------	--