

FORM
5A
Rev
06/12

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:
400497406

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>69175</u>	4. Contact Name: <u>Cassie Gonzalez</u>
2. Name of Operator: <u>PDC ENERGY INC</u>	Phone: <u>(303) 860-5800</u>
3. Address: <u>1775 SHERMAN STREET - STE 3000</u>	Fax: <u>(303) 831-3988</u>
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80203</u>	Email: <u>Cassie.Gonzalez@pdce.com</u>

5. API Number <u>05-123-35446-00</u>	6. County: <u>WELD</u>
7. Well Name: <u>Spaur</u>	Well Number: <u>31W-214</u>
8. Location: QtrQtr: <u>NENE</u> Section: <u>31</u> Township: <u>7N</u> Range: <u>63W</u> Meridian: <u>6</u>	
9. Field Name: <u>WATTENBERG</u> Field Code: <u>90750</u>	

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 09/21/2012 End Date: 09/21/2012 Date of First Production this formation: 09/29/2012
Perforations Top: 7265 Bottom: 11100 No. Holes: Hole size:

Provide a brief summary of the formation treatment: Open Hole:

16 Stage Sliding Sleeve, Swell Packer set @ 7,265'
Total Fluid: 58,894 bbls
Gel Fluid: 47,764 bbls
Slickwater Fluid: 11,130 bbls
Total Proppant: 3,662,089 lbs
Silica Proppant: 3,662,089 lbs
Method for determining flowback: measuring flowback tank volumes.

This formation is commingled with another formation: Yes No

Total fluid used in treatment (bbl): 58894 Max pressure during treatment (psi): 3546
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34
Type of gas used in treatment: Min frac gradient (psi/ft): 0.94
Total acid used in treatment (bbl): Number of staged intervals: 16
Recycled water used in treatment (bbl): Flowback volume recovered (bbl): 5151
Fresh water used in treatment (bbl): 58894 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 3662089 Rule 805 green completion techniques were utilized:
Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 10/10/2012 Hours: 24 Bbl oil: 115 Mcf Gas: 211 Bbl H2O: 75
Calculated 24 hour rate: Bbl oil: 115 Mcf Gas: 211 Bbl H2O: 75 GOR: 1835
Test Method: Flowing Casing PSI: 967 Tubing PSI: 582 Choke Size: 32/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1318 API Gravity Oil: 43
Tubing Size: 2 + 3/8 Tubing Setting Depth: 6940 Tbg setting date: 09/27/2012 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: Yes No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.
Signed: Print Name: Cassie Gonzalez
Title: Regulatory Technician Date: Email: Cassie.Gonzalez@pdce.com

Attachment Check List

Att Doc Num	Name

Total Attach: 0 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Returned to draft for AOC settlement.	09/15/2016

Total: 1 comment(s)