



SRC ENERGY

Reviewed: 5/28/19 CD

Operator:	SRC Energy		
Well Name:	Severin 2		
Legal:	NWSW, Section 4, Township 6N, Range 66W		
Location:	Weld County, CO		
API:	05-123-11142		
Surface:	8.625" 24# @ 350'	Hole Size: 9.875"	TOC: Surface
Production:	4.5" 9.5# @ 7,350'	Hole Size: 7.875"	TOC: 6,350' (Calc.)
Perforations:	7,300' – 7,318' (Codell)		
TD:	7,400'		

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 9.5# CIBP, set at 7,225'
6. Pressure test casing to 500 psi for 15 minutes. If does not pass note csg. repair that was performed at 2941' in 2017.
7. Run CBL
8. Set 36 sx on top of CIBP (cover 206' above Niobrara top)
9. Set 32 sx at 3141' (400' plug)
10. Cut 4-1/2" casing at 950' and POOH
11. TIH to 991' and pump stub plug (0' – 1000')
 - a. 313 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 650' out of surface casing
 - c. Wait 4 hours and tag plug
12. RDMO WO unit
13. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
14. Weld on cap with ID plate, inscribed with well location, and identity
15. Backfill, clean location
16. P&A complete