



SRC ENERGY

Reviewed: 5/21/19 CD

Operator: SRC Energy
Well Name: Roy A. Schmidt Unit 1
Legal: SESE, Section 25, Township 4N, Range 66W
Location: Weld County, CO
API: 05-123-09100
Surface: 8.625" 24# @ 500' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 10.5# @ 4642' **Hole Size:** 7.875" **TOC:** 3842' (Calc)
Perforations: 4508'-4549' (Sussex)
TD: 4650'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 10.5# CIBP, set at 4433'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 12 sx on top of CIBP (cover 215' above Sussex top)
8. TIH to 2500' and perforate casing
9. TIH w/ 4-1/2" 10.5# CICR, set at 2400'
 - a. Squeeze perfs w/ 68 sx (300' annulus plug & 100' casing plug)
 - b. Release off of CICR and set 8 sx on top (100' plug)
10. Cut 4.5" casing at 936' and POOH
11. TIH to 986' and pump stub plug (986' – 0')
 - a. 299 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 486' out of surface casing
12. RDMO WO unit
13. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
14. Weld on cap with ID plate, inscribed with well location, and identity
15. Backfill, clean location
16. P&R complete