



SRC ENERGY

Reviewed: 6/6/19 CD

Operator: SRC Energy
Well Name: LH Miller Unit #2
Legal: SESW, Section 25, Township 4N, Range 66W
Location: Weld County, CO
API: 05-123-15330
Surface: 8.625" 24# @ 539' **Hole Size:** 12.25" **TOC:** Surface
Production: 5.5" 17# @ 4,664' **Hole Size:** 7.875" **TOC:** 2481' (Calc)
Perforations: 4,466 – 4,518' (Sussex)
TD: 4,673'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 5.5" 17# CIBP set at **4391'**
6. Perform CBL from 4390' to surface
7. Pressure test casing to 500 psi for 15 minutes
8. Pump 18 **sx** on top of CIBP
9. TIH to **2400'** and perforate casing
10. TIH w/ 5-1/2" 17# CICR, set at **2,300'**
 - a. Squeeze perms w/ **58 sx**
 - b. Release off of CICR and set **12 sx** on top
11. Cut 5.5" casing at **850'** and POOH
12. TIH to **900'** and pump stub plug
 - a. **275 sx** of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Pull into surface casing
 - c. Wait 4 hours and tag plug
13. RDMO WO unit
14. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
15. Weld on cap with ID plate, inscribed with well location, and identity
16. Backfill, clean location
17. P&R complete