

Operator:	SRC Energy	Reviewed: 5/30/2019 CD	
Well Name:	ELMER W SCHMIDT UNIT #2		
Legal:	SWSW 30 4N 65W		
Location:	Weld County, CO		
API:	05-123-09734		
Surface:	8.625" 23# @ 426'	Hole Size: 12.25"	TOC: Surface
Production:	4.5" 11.6# @ 4620'	Hole Size: 7.875"	TOC: 3651' (CALC)
Perforations:	4482 - 4586 SUSSEX		
TD:	4656		

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 10.5# CIBP on tubing, set at 4407'
7. Set 15 sx on top of existing CIBP (200')
8. Spot 15 sx (200') plug with from 4147 - 4347
9. TIH w/perf gun to 2500' and perforate casing
10. TIH w/ 4-1/2" 10.5# CICR, set at 2400'
 - a. pump 84 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Release off of CICR and pump 9 sx (120' casing plug)
11. Cut 4.5" casing @ 968'
12. TIH with tubing to 1018' and pump stub plug from 0 - 1018'
 - a. pump 317 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
13. RDMO WO unit
14. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
15. Weld on cap with ID plate, inscribed with well location, and identity
16. Backfill, clean location
17. P&R complete