



SRC ENERGY

Reviewed: 6/6/19

Operator: SRC Energy
Well Name: Elmer W Schmidt Unit #1
Legal: NWNW, Section 30, Township 4N, Range 65W
Location: Weld County, CO
API: 05-123-08923
Surface: 8.625" 24# @ 486' **Hole Size:** 12.25"
Production: 4.5" 11.6# @ 4,618' **Hole Size:** 7.875" **TOC:** Surface
Perforations: 4,481 – 4,508' (Sussex) **TOC:** 3700' Est (CBL)
TD: 4,618'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP set at **4420'**
6. Pump 15 **sx** on top of CIBP
7. TIH to **2,500'** and perforate casing
8. TIH w/ 4-1/2" 11.6# CICR, set at **2,400'**
 - a. Squeeze perfs w/ **70 sx**
 - b. Release off of CICR and set **15 sx** on top
9. Cut 4.5" casing at **850'** and POOH
10. TIH to **900'** and pump stub plug
 - a. **295 sx** of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Pull into surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&R complete