

*The Road to Excellence Starts with Safety*

Sold To #: 343492		Ship To #: 3917348		Quote #:		Sales Order #: 0905562054				
Customer: HIGHPOINT RESOURCES CORP-EBUS				Customer Rep: KC						
Well Name: WETCO		Well #: 4-63-05-5764DB		API/UWI #: 05-123-48493-00						
Field: WATTENBERG		City (SAP): KERSEY		County/Parish: WELD		State: COLORADO				
Legal Description: NW SW-4-4N-63W-2200FSL-701FWL										
Contractor: CADE DRLG				Rig/Platform Name/Num: CADE 23						
Job BOM: 7522 7522										
Well Type: HORIZONTAL OIL										
Sales Person: HALAMERICA\H139013				Srvc Supervisor: Prince Perez						
Job										
Formation Depth (MD)		Top 0'		Bottom		7,399'				
Job depth MD		7,384'		Job Depth TVD		6,539'				
Water Depth				Wk Ht Above Floor		5'				
Well Data										
Description	New / Used	Size in	ID in	Weight lbrn/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft
Casing		9.625	8.921	36			0	822	0	822
Casing		7	6.366	23			0	7385	0	6539
Open Hole Section			8.75				822	7399	822	6539
Tools and Accessories										
Type	Size in	Qty	Make	Depth ft		Type	Size in	Qty	Make	
Guide Shoe	7	1		7,385		Top Plug	7	1		
Float Shoe	7					Bottom Plug	7	0		
Float Collar	7	1		7,337.7'		SSR plug set	7			
Insert Float	7					Plug Container	7	1	HES	
Stage Tool	7					Centralizers	7	10	STKMN	
Fluid Data										
Stage/Plug #: 1										
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbrn/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
1	Spacer	Red Dye	25	bbl	8.33					
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbrn/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
2	Cement	ELASTICEM (TM) SYSTEM	815	sack	13.2	1.57	7.53	8	6,137	

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
3	Displacement	Fesh Water	288.4	bbl	8.33				
Cement Left In Pipe		Amount	47 ft		Reason			Shoe Joint	
Mix Water:		pH 7	Mix Water Chloride:		<300 ppm		Mix Water Temperature:		65 °F
Cement Temperature:		## °F	Plug Displaced by:		8.33 lb/gal		Disp. Temperature:		65 °F
Plug Bumped?		Yes	Bump Pressure:		1,728 psi		Floats Held?		Yes
Cement Returns:		0 bbl	Returns Density:		9.9 lb/gal		Returns Temperature:		## °F
<b>Comment</b> Pumped 25 bbls of Red Dye Spacer. Pumped 227.89 bbls of Elasticem. Pumped 288.4 bbls of fresh water Displacement. No spacer to surface. 3 bbls back on the floats.									

# Summary Report

Crew: \_\_\_\_\_  
Job Start Date: 03/20/2019 01:00 AM

Sales Order #: 0905562054  
WO #: 0905562054  
PO #: NA  
AFE #: 20333D

Customer:	HIGHPOINT RESOURCES CORP- EBUS	Field:	WATTENBERG	Job Type:	CMT INTERMEDIATE CASING BOM
UWI / API Number:	05-123-48493-00	County/Parish:	WELD	Service Supervisor:	Prince Perez
Well Name:	WETCO	State:	COLORADO		
Well No:	4-63-05-5764DB	Latitude:	40.339824	Cust Rep Name:	KC
		Longitude:	-104.449947	Cust Rep Phone #:	
		Sect / Twn / Rng:	4/4/63		

**Remarks:**

<b>The Information Stated Herein Is Correct</b>	Customer Representative Signature	Date
	Customer Representative Printed Name	