



SRC ENERGY

Reviewed: 6/20/19 CD

Operator: SRC Energy
Well Name: CJ Schmidt Unit #2
Legal: NWNE, Section 19, Township 4N, Range 65W
Location: Weld County, CO
API: 05-123-09452
Surface: 8.625" 24# @ 350' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 10.5# @ 4527' **Hole Size:** 7.875" **TOC:** 2366' (CBL)
Perforations: 4408'-4450' (Sussex)
TD: 4585'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 10.5# CIBP, set at 4255'
6. Run CBL from 4025' to surface
7. Pressure test casing to 500 psi for 15 minutes
8. Set 16 sx on top of CIBP (cover 275' above Niobrara top)
9. Perf @ 2500', set CICR @ 2400'
10. Pump 68 sxs through CICR (300' annular plug)
11. Set 16 sxs on CICR (200')
12. Cut 4.5" casing at 900' and POOH
13. TIH to 950' and pump stub plug (0' – 950')
 - a. 286 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 600' out of surface casing
 - c. Wait 4 hours and tag plug
14. RDMO WO unit
15. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
16. Weld on cap with ID plate, inscribed with well location, and identity
17. Backfill, clean location
18. P&R complete