

OIL AND GAS CONSERVATION COMMISSION OF THE STATE OF COLORADO

RECEIVED MAR 15 1963

PLUGGING RECORD

OIL & GAS CONSERVATION COMMISSION



INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator W. C. McBride, Inc. Field Wildcat X
Lease Name State Well No. 2 County Larimer
Location SW NW Section 36 Township 9N Range 69W Meridian 6th
2080 feet from N Section line and 660 feet from W Section Line
N or S E or W

TOTAL DEPTH 5772 DATE OF PLUGGING February 20, 1963

DETAILS OF WORK

This well was plugged with 15 sacks regular cement overlapping open-hole and bottom of surface casing. Ten sacks of regular cement were placed in the top of the surface casing and a steel plate was welded over the top of the surface casing. Heavy mud was left in the hole below the bottom cement plug and between the two cement plugs with the following properties: Density 9.8#/gal, Vis 47 seconds per quart.

Location checked on 5/21/63, Jim

Table with 2 columns and 6 rows: DVR, WRS, HHM, JAM, FJP, JJD, FILE. JAM, FJP, and JJD have checkmarks.

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved: Date MAR 18 1963
Company W. C. McBride, Inc. Date March 12, 1963
Address 620 Colo. Bldg., Denver 2 Phone No. TA 5-2366
By David Pauli Title Prod. Supt.
Director (Signature)

5