



SRC ENERGY

Reviewed: 7/2/19 CD

Operator: SRC Energy
Well Name: Kawata 15-22
Legal: NWNW, Section 15, Township 4N, Range 66W
Location: Weld County, CO
API: 05-123-16259
Surface: 8.625" 24# @ 387' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 15.1# @ 7,376' **Hole Size:** 7.875" **TOC:** 4160' (CBL)
Perforations: 6916' – 7126' (Niobrara); 7,232' – 7,242' (Codell)
TD: 7,380'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 15.1# CIBP set at 6837'
6. Run CBL from 6800' to surface
7. Pressure test casing to 500 psi for 15 minutes
8. Pump 11 sx on top of CIBP **(225' Niobrara coverage)**
9. RIH to 4432' and pump 21 sxs cement **(300' Sussex coverage)**
10. Perforate @ 2400', establish circulation rate
11. Set CICR @ 2300',
12. Pump 67 sx through CICR, set 14 sx on top
13. Cut 4.5" casing at **800'** and POOH
14. TIH to **850'** and pump stub plug
 - a. **260 sx** of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Pull into surface casing
 - c. Wait 4 hours and tag plug
15. RDMO WO unit
16. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
17. Weld on cap with ID plate, inscribed with well location, and identity
18. Backfill, clean location
19. P&R complete