

FORM  
5A

Rev  
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

402156072

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 69175

2. Name of Operator: PDC ENERGY INC

3. Address: 1775 SHERMAN STREET - STE 3000

City: DENVER State: CO Zip: 80203

4. Contact Name: Cassie Gonzalez

Phone: (303) 860-5800

Fax:

Email: Cassie.Gonzalez@pdce.com

5. API Number 05-123-45254-00

7. Well Name: Thistle Down

8. Location: QtrQtr: NESW Section: 31 Township: 5N Range: 64W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 31H-202

## Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/27/2019 End Date: 07/06/2019 Date of First Production this formation: 08/12/2019  
Perforations Top: 7246 Bottom: 12848 No. Holes: 1122 Hole size: 42/100

Provide a brief summary of the formation treatment:

Open Hole: ☐

32 Stage Plug and Perf  
Total Fluid: 113,444 bbls  
Gel Fluid: 78,467 bbls  
Slickwater Fluid: 34,166 bbls  
15% HCl Acid: 811 bbls  
Total Proppant: 6,260,740 lbs  
Silica Proppant: 6,260,740 lbs  
Method for determining flowback: measuring flowback tank volumes.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 113444

Max pressure during treatment (psi): 4190

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.95

Total acid used in treatment (bbl): 811

Number of staged intervals: 32

Recycled water used in treatment (bbl):

Flowback volume recovered (bbl): 5154

Fresh water used in treatment (bbl): 112633

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 6260740

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

### Test Information:

Date: 08/18/2019 Hours: 24 Bbl oil: 343 Mcf Gas: 1526 Bbl H2O: 188  
Calculated 24 hour rate: Bbl oil: 343 Mcf Gas: 1526 Bbl H2O: 188 GOR: 4449  
Test Method: Flowing Casing PSI: 2689 Tubing PSI: 1876 Choke Size: 16/64  
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1302 API Gravity Oil: 53  
Tubing Size: 2 + 3/8 Tubing Setting Depth: 7142 Tbg setting date: 08/05/2019 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

Actual Top of Productive Zone Footage: 1,455' FSL & 468' FWL Sec: 31 Twp: 5N Rng: 64W

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Cassie Gonzalez

Title: Regulatory Technician Date: Email: Cassie.Gonzalez@pdce.com

## Attachment Check List

Att Doc Num Name

Total Attach: 0 Files

## General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)