Interchange B N 35-20 BC

Company: Chevron
Well: Interchange B N 35-20 BC
Field: Interchange
Location: Sec 35 T 20 S R 21 E
County: Grand
State: Utah
API Number: 43-019-31599
Engineer: Mike Stevens
Witness: Mike Stevens
Service Company: Weatherford

Well Head Coordinates: N/S: 0.00 ft, E/W: 0.00 ft
Datum Elevation: 4,722.00 ft (KB)
Permanent Datum: Ground Level
Log Measured From: KB, 0.00 ft above Permanent Datum
Drilling Measured From: KB

Run	Service	Date	Depth Driller	Depth Logger
1	Weatherford	10/31/2006	6,000.00 ft	6,000.00 ft

Bottom Log Interval: 6,000.00 ft
Top Log Interval: 0.00 ft
Casing Driller Size at Depth: 9.625 in @ 0.00 ft
Casing Logger Size at Depth: 9.625 in @ 0.00 ft
Bit Size: 8.750 in
Type Fluid in Hole: Water
Density: 8.40 lb/gal
Viscosity: 26.00 s/qt
PH: 7.00
Fluid Loss: 0.00 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.00 ohm-m @ 0.00 °F
Rmf @ Measured Temp: 0.00 ohm-m @ 0.00 °F
Rmc @ Measured Temp: 0.00 ohm-m @ 0.00 °F
Source of Rmf/Rmc: Measured
Rm @ BHT: 0.00 ohm-m @ 0.00 °F
Time Since Circulation: 0.00 hr
Max Recorded Temp: 0.00 °F
Equipment Number: 0
Location: 0
Recorded By: Mike Stevens
Witnessed By: Mike Stevens

Run	Top	Bottom	Tool Type	Tool Number	Diameter	Length	Weight	Density	Viscosity	Resistivity	Temperature	Fluid Loss
1	0.00 ft	6,000.00 ft	Dual Induction Focused Log	0	3.625 in	0.00 ft	0.00 lb/ft	8.40 lb/gal	26.00 s/qt	0.00 ohm-m	0.00 °F	0.00 cc
1	0.00 ft	6,000.00 ft	Compensated Density Neutron	0	3.625 in	0.00 ft	0.00 lb/ft	8.40 lb/gal	26.00 s/qt	0.00 ohm-m	0.00 °F	0.00 cc
1	0.00 ft	6,000.00 ft	Array Sonic	0	3.625 in	0.00 ft	0.00 lb/ft	8.40 lb/gal	26.00 s/qt	0.00 ohm-m	0.00 °F	0.00 cc
1	0.00 ft	6,000.00 ft	Gamma Ray	0	3.625 in	0.00 ft	0.00 lb/ft	8.40 lb/gal	26.00 s/qt	0.00 ohm-m	0.00 °F	0.00 cc

Gamma Ray (GR) 0 API 200
Caliper (CALI) 6 in 16
Deep Resistivity (RILD) 0.2 ohm-m 2000
Medium Resistivity (RILM) 0.2 ohm-m 2000
Shallow Resistivity (RILS) 0.2 ohm-m 2000
Density Porosity (DPHI) 0.45 v/v -0.15
Neutron Porosity (NPHI) 0.45 v/v -0.15
Bulk Density (RHOB) 1.95 g/cm3 2.95
Delta Rho (DRHO) -0.25 g/cm3 0.25
Photoelectric Factor (PEF) 0 b/e 10
Delta-T Compressional (DTCO) 140 us/ft 40
Delta-T Shear (DTSM) 240 us/ft 90
Delta-T Compressional (DTCO) 140 us/ft 40
Delta-T Shear (DTSM) 240 us/ft 90
Gamma Ray (GR) 0 API 200
Caliper (CALI) 6 in 16
Deep Resistivity (RILD) 0.2 ohm-m 2000
Medium Resistivity (RILM) 0.2 ohm-m 2000
Shallow Resistivity (RILS) 0.2 ohm-m 2000
Density Porosity (DPHI) 0.45 v/v -0.15
Neutron Porosity (NPHI) 0.45 v/v -0.15
Bulk Density (RHOB) 1.95 g/cm3 2.95
Delta Rho (DRHO) -0.25 g/cm3 0.25
Photoelectric Factor (PEF) 0 b/e 10
Delta-T Compressional (DTCO) 140 us/ft 40
Delta-T Shear (DTSM) 240 us/ft 90
Gamma Ray (GR) 0 API 200
Caliper (CALI) 6 in 16
Deep Resistivity (RILD) 0.2 ohm-m 2000
Medium Resistivity (RILM) 0.2 ohm-m 2000
Shallow Resistivity (RILS) 0.2 ohm-m 2000
Density Porosity (DPHI) 0.45 v/v -0.15
Neutron Porosity (NPHI) 0.45 v/v -0.15
Bulk Density (RHOB) 1.95 g/cm3 2.95
Delta Rho (DRHO) -0.25 g/cm3 0.25
Photoelectric Factor (PEF) 0 b/e 10
Delta-T Compressional (DTCO) 140 us/ft 40
Delta-T Shear (DTSM) 240 us/ft 90








Time
Time
Time
Time