

# HALLIBURTON

iCem<sup>®</sup> Service

**EXTRACTION OIL & GAS**

**Interchange B N35-20-9N**

Sincerely,

**Alexandria Dionigi**

## Legal Notice

---

### Disclaimer:

All information in this report is provided subject to the terms and conditions which govern the services provided by Halliburton. Halliburton personnel use their best efforts in gathering information and their best judgment in interpreting it, but any interpretation, research, analysis or recommendation furnished by Halliburton are opinions based upon inferences from measurements and empirical relationships and assumptions, which inferences and empirical relationships and assumptions are not infallible, and with respect to which professionals in the industry may differ. iCem 3D Displacement results are used to understand how fluids intermix during a cement job. Simulation and 3D displacement results are not intended as and should not be used as a replacement for bond logs in determining top of cement. Current 3D model calculations are known to model more volume than the input volume for standard cases due to known calculation improvements required. For rotational cases, the modeled volume will be impacted by the same calculations impacting the standard cases, as well as additional constraints imposed to make the calculation time required operationally feasible. Therefore, until further notice, 3D displacement results should not be used for replacement of a bond log, or used as an identifier of top of cement. HALLIBURTON IS UNABLE TO GUARANTEE THE ACCURACY OF ANY CHART INTERPRETATION, RESEARCH ANALYSIS, OR JOB RECOMMENDATION and any interpretation or recommendation is not for use of or reliance upon by any third party. The customer has full responsibility for any of its decisions which are based on the information provided in this report.

## Table of Contents

---

1.0	Cementing Job Summary .....	4
1.1	Executive Summary .....	4
2.0	Real-Time Job Summary .....	7
2.1	Job Event Log .....	7
3.0	Attachments.....	9
3.1	Case 1-Custom Results.png.....	9

## 1.0 Cementing Job Summary

---

### 1.1 Executive Summary

---

Halliburton appreciates the opportunity to perform the cementing services on the **Interchange B N35-20-9N** cement **Production** casing job. A pre-job safety meeting was held before the job where details of the job were discussed, potential safety hazards were reviewed, and environmental compliance procedures were outlined.

**Approximately 63 bbls of cement were returned to surface.**

Halliburton maintains a continuous quality improvement process and appreciates any comments or suggestions that you may have. Halliburton again thanks you for the opportunity to perform service work on this well. We hope to be your solutions provider for future projects.

Respectfully,

**Halliburton Fort Lupton**

*The Road to Excellence Starts with Safety*

<b>Sold To #:</b> 369404	<b>Ship To #:</b> 3901403	<b>Quote #:</b>	<b>Sales Order #:</b> 0905746710
<b>Customer:</b> EXTRACTION OIL & GAS-EBUS		<b>Customer Rep:</b> Manny	
<b>Well Name:</b> INTERCHANGE B		<b>Well #:</b> N35-20-9N	<b>API/UWI #:</b> 05-014-20773-00
<b>Field:</b> WATTENBERG	<b>City (SAP):</b> BROOMFIELD	<b>County/Parish:</b> BROOMFIELD	<b>State:</b> COLORADO
<b>Legal Description:</b> NE SW-10-1S-68W-2509FSL-1690FWL			
<b>Contractor:</b> PATTERSON-UTI ENERGY		<b>Rig/Platform Name/Num:</b> PATTERSON 901	
<b>Job BOM:</b> 7523 7523			
<b>Well Type:</b> HORIZONTAL OIL			
<b>Sales Person:</b> HALAMERICA\HX38199		<b>Srvc Supervisor:</b> Nathaniel Moore	

**Job**

<b>Formation Name</b>	
<b>Formation Depth (MD)</b>	<b>Top</b> <input type="text"/> <b>Bottom</b> <input type="text"/>
<b>Form Type</b>	BHST
<b>Job depth MD</b>	18672ft <b>Job Depth TVD</b> 7640
<b>Water Depth</b>	<b>Wk Ht Above Floor</b>
<b>Perforation Depth (MD)</b>	<b>From</b> <input type="text"/> <b>To</b> <input type="text"/>

**Well Data**

Description	New / Used	Size in	ID in	Weight lbm/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft
Casing	0	9.625	8.921	36			0	1662	0	1662
Casing	0	5.5	4.892	17	BTC	P-110	0	18668	0	7640
Open Hole Section			8.75				1662	18672	1662	7640

**Tools and Accessories**

Type	Size in	Qty	Make	Depth ft	Type	Size in	Qty	Make
Guide Shoe	5.5				Top Plug	5.5		HES
Float Shoe	5.5			18668	Bottom Plug	5.5		HES
Float Collar	5.5				SSR plug set	5.5		HES
Insert Float	5.5				Plug Container	5.5		HES
Stage Tool	5.5				Centralizers	5.5		HES

**Fluid Data**

<b>Stage/Plug #: 1</b>										
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft <sup>3</sup> /sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal	
1	FDP-C1337-18	SBM FDP-C1337-18 CEMENT SPACER SYS	50	bbl	12.5	2.74		6		
	5 lbm/bbl	SEM-94P, 35 LB SACK - (1023987)								
	205.22 lbm/bbl	BARITE, BULK (100003681)								
	5 lbm/bbl	SEM-93P, 35 LB SACK - (1023977)								
	1 lbm/bbl	FE-2 (100001615)								

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft <sup>3</sup> /sack	Mix Fluid Gal	Rate bbl/mi n	Total Mix Fluid Gal
2	ElastiCem	ELASTICEM (TM) SYSTEM	586	sack	13.2	1.6		8	7.75
0.75 %		SCR-100 (100003749)							
7.75 Gal		FRESH WATER							
3	GasStop	ELASTICEM (TM) SYSTEM	615	sack	13.2	1.6		8	7.74
0.75 %		SCR-100 (100003749)							
5.24 Gal		FRESH WATER							
4	ElastiCem	ELASTICEM (TM) SYSTEM	1769	sack	13.2	1.57		8	7.66
0.75 %		SCR-100 (100003749)							
7.66 Gal		FRESH WATER							
5	MMCR Displacement	MMCR Displacement	40	bbl	8.33			8	
0.50 gal/bbl		MICRO MATRIX CEMENT RETARDER, 5 GAL PAIL (100003781)							
1 gal/bbl		D-AIR 3000L, 5 GAL PAIL (101007444)							
6	Displacement	Displacement	339.2	bbl	8.33			8	
<b>Cement Left In Pipe</b>	<b>Amount</b>	0 ft			<b>Reason</b>			Shoe Joint	
<b>Mix Water:</b>	pH 7	<b>Mix Water Chloride:</b>	<300 ppm			<b>Mix Water Temperature:</b>	60 °F		
<b>Cement Temperature:</b>	## °F °C	<b>Plug Displaced by:</b>	Water			<b>Disp. Temperature:</b>	## °F °C		
<b>Plug Bumped?</b>	Yes	<b>Bump Pressure:</b>	2350 to 2650psi			<b>Floats Held?</b>	Yes/No		
<b>Cement Returns:</b>	63 bbl	<b>Returns Density:</b>	#13.2 lb/gal			<b>Returns Temperature:</b>	## °F °C		
<b>Comment</b> Pumped 5 bbl wet shoe									

## 2.0 Real-Time Job Summary

### 2.1 Job Event Log

Type	Seq. No.	Activity	Graph Label	Date	Time	Source	DS Pump Press <i>(psi)</i>	DH Density <i>(ppg)</i>	Comb Pump Rate <i>(bbl/min)</i>	Pump Stg Tot <i>(bbl)</i>	Comments
Event	1	Call Out	Call Out	6/5/2019	08:00:00	USER					OL time 1300. Verify equipment and materials
Event	2	Depart Yard Safety Meeting	Depart Yard Safety Meeting	6/5/2019	11:30:00	USER					Journey management conducted
Event	3	Assessment Of Location Safety Meeting	Assessment Of Location Safety Meeting	6/5/2019	12:30:00	USER					Sign in with customer rep. Spot in and rig up equipment.
Event	4	Event	Meet with customer rep	6/5/2019	13:00:00	USER					TD 18672' 8.5" hole. TP 18668' 5.5" 20# Casing. SJ 5'. TVD 7640'. SC 1662'. MW 9.5 ppg.
Event	5	Safety Meeting - Pre Job	Safety Meeting - Pre Job	6/5/2019	18:45:00	USER	-22.00	8.26	0.00	0.00	Discuss job procedure with HES and rig crew
Event	6	Test Lines	Test Lines	6/5/2019	19:09:29	COM4	-12.00	8.17	0.00	1.60	500 psi kickout test and 5000 psi pressure test
Event	7	Pump Spacer 1	Pump Spacer 1	6/5/2019	19:21:51	COM4	-16.00	8.23	0.00	1.70	50 bbl FDP spacer with dry surfactants. 12.5 ppg 2.74 ft3/sk 16.6 gal/sk
Event	8	Drop Bottom Plug	Drop Bottom Plug	6/5/2019	19:22:48	COM4	145.00	10.05	2.60	1.20	NCS tools bottom plug
Event	9	Pump Lead Cement	Pump Lead Cement	6/5/2019	19:35:30	USER	140.00	12.53	5.00	41.30	586 sks/167 bbl ElastiCem with Bridgmaker 13.2 ppg 1.6 ft3/sk 7.75 gal/sk
Event	10	Pump Lead Cement	Pump Lead Cement	6/5/2019	20:15:57	COM4	587.00	13.25	7.00	234.90	615 sks/175 bbl GasStop with Bridgemaker 13.2 ppg 1.6 ft3/sk 7.75 gal/sk

Event	11	Check Weight	Check Weight	6/5/2019	20:15:59	COM4	581.00	13.26	7.00	0.20	13.2 ppg verified with pressurized scales
Event	12	Pump Tail Cement	Pump Tail Cement	6/5/2019	20:42:33	COM4	716.00	13.20	7.00	0.10	1769 sks ElastiCem Tail 13.2 ppg 1.57 ft3/sk 7.66 gal/sk
Event	13	Check Weight	Check Weight	6/5/2019	20:46:31	COM4	538.00	13.27	7.00	29.50	13.2 ppg
Event	14	Event	Land bottom plug	6/5/2019	20:50:39	USER	535.00	13.24	6.90	58.30	Land bottom plug and burst at 850 psi
Event	15	Shutdown	Shutdown	6/5/2019	21:59:00	USER	240.00	13.03	4.60	517.40	
Event	16	Clean Lines	Clean Lines	6/5/2019	21:59:26	COM4	44.00	13.90	0.00	518.40	Shutdown and wash pumps and lines. Blow cement back to washup tank with rig air.
Event	17	Drop Top Plug	Drop Top Plug	6/5/2019	22:07:31	COM4	-29.00	1.60	0.00	543.60	NCS Top plug verified by tool hand and company rep
Event	18	Pump Displacement	Pump Displacement	6/5/2019	22:07:37	COM4	-33.00	0.86	0.00	543.60	432 bbl water displacement with MMCR in first 20 bbl
Event	19	Other	Spacer to surface	6/5/2019	22:55:01	COM4	2684.00	8.18	6.00	335.40	Spacer to surface. 320 bbl into displacment. 50 bbl spacer back.
Event	20	Other	Cement to surface	6/5/2019	23:04:30	COM4	2707.00	8.19	6.00	392.10	370 bbl into displacment. 62 bbl cement back.
Event	21	Bump Plug	Bump Plug	6/5/2019	23:16:42	COM4	2915.00	8.20	1.50	438.00	Final circulating pressure 2350 psi. Pressured up to 2650 and held for 2 minutes. Shifted wet shoe at 3200 psi and pumped 5 bbl wet shoe.
Event	22	Check Floats	Check Floats	6/5/2019	23:19:07	USER	731.00	8.16	0.00	445.20	3 bbl back. Floats held.
Event	23	Pre-Rig Down Safety Meeting	Pre-Rig Down Safety Meeting	6/5/2019	23:30:00	USER					
Event	24	Depart Location Safety Meeting	Depart Location Safety Meeting	6/6/2019	01:30:00	USER					

## 3.0 Attachments

### 3.1 Case 1-Custom Results.png

