

HALLIBURTON

iCem[®] Service

EXTRACTION OIL & GAS

Interchange B N35-20-5C Production

Sincerely,
Meghan Jacobs

Legal Notice

Disclaimer:

All information in this report is provided subject to the terms and conditions which govern the services provided by Halliburton. Halliburton personnel use their best efforts in gathering information and their best judgment in interpreting it, but any interpretation, research, analysis or recommendation furnished by Halliburton are opinions based upon inferences from measurements and empirical relationships and assumptions, which inferences and empirical relationships and assumptions are not infallible, and with respect to which professionals in the industry may differ. iCem 3D Displacement results are used to understand how fluids intermix during a cement job. Simulation and 3D displacement results are not intended as and should not be used as a replacement for bond logs in determining top of cement. Current 3D model calculations are known to model more volume than the input volume for standard cases due to known calculation improvements required. For rotational cases, the modeled volume will be impacted by the same calculations impacting the standard cases, as well as additional constraints imposed to make the calculation time required operationally feasible. Therefore, until further notice, 3D displacement results should not be used for replacement of a bond log, or used as an identifier of top of cement. HALLIBURTON IS UNABLE TO GUARANTEE THE ACCURACY OF ANY CHART INTERPRETATION, RESEARCH ANALYSIS, OR JOB RECOMMENDATION and any interpretation or recommendation is not for use of or reliance upon by any third party. The customer has full responsibility for any of its decisions which are based on the information provided in this report.

Table of Contents

1.0	Cementing Job Summary	4
1.1	Executive Summary	4
2.0	Real-Time Job Summary	7
2.1	Job Event Log	7
3.0	Attachments.....	9
3.1	Interchange B N35-20-5C Production – Start of Job Chart	9
3.2	End of Job Chart.....	10

1.0 Cementing Job Summary

1.1 Executive Summary

Halliburton appreciates the opportunity to perform the cementing services on the **Interchange B N35-20-5C** cement **Production** casing job. A pre-job safety meeting was held before the job where details of the job were discussed, potential safety hazards were reviewed, and environmental compliance procedures were outlined.

Approximately 54 bbls of cement were returned to surface.

Halliburton maintains a continuous quality improvement process and appreciates any comments or suggestions that you may have. Halliburton again thanks you for the opportunity to perform service work on this well. We hope to be your solutions provider for future projects.

Respectfully,

Halliburton Fort Lupton

The Road to Excellence Starts with Safety

Sold To #: 369404		Ship To #: 3901349		Quote #:		Sales Order #: 0905692511				
Customer: EXTRACTION OIL & GAS-EBUS					Customer Rep: Manny Parras					
Well Name: INTERCHANGE B			Well #: N35-20-5C			API/UWI #: 05-014-20772-00				
Field: WATTENBERG		City (SAP): BROOMFIELD		County/Parish: BROOMFIELD			State: COLORADO			
Legal Description: NE SW-10-1S-68W-2492FSL-1620FWL										
Contractor: PATTERSON-UTI ENERGY					Rig/Platform Name/Num: PATTERSON 901					
Job BOM: 7523 7523										
Well Type: HORIZONTAL OIL										
Sales Person: HALAMERICA\HX38199					Srvc Supervisor: Thomas Haas					
Job										
Formation Name										
Formation Depth (MD)		Top			Bottom					
Form Type					BHST					
Job depth MD		18705ft			Job Depth TVD		8045			
Water Depth					Wk Ht Above Floor		5			
Perforation Depth (MD)		From			To					
Well Data										
Description	New / Used	Size in	ID in	Weight lbm/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft
Casing	0	9.625	8.921	36			0	1652	0	1652
Casing	0	5.5	4.892	17	BTC	P-110	0	18705	0	8045
Open Hole Section			8.75				1652	18720	1652	8045
Tools and Accessories										
Type	Size in	Qty	Make	Depth ft		Type	Size in	Qty	Make	
						Top Plug	5.5	1	NCS	
Float Shoe	5.5	1	NCS	18705		Bottom Plug	5.5	1	NCS	
Float Collar	5.5	1	NCS	18700						
						Plug Container	5.5	1	HES	
Fluid Data										
Stage/Plug #: 1										

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
1	FDP-C1337-18	SBM FDP-C1337-18 CEMENT SPACER SYS	50	bbl	12.5	2.74	16.6	8	1701
2	ElastiCem	ELASTICEM (TM) SYSTEM	585	sack	13.2	1.6	7.75	8	4534
3	GasStop	ELASTICEM (TM) SYSTEM	615	sack	13.2	1.6	7.7	8	4736
4	ElastiCem	ELASTICEM (TM) SYSTEM	1128	sack	13.2	1.57	7.66	8	13351
5	MMCR Displacement	MMCR Displacement	20	bbl	8.33			8	
0.50 gal/bbl		MICRO MATRIX CEMENT RETARDER, 5 GAL PAIL (100003781)							
6	Displacement	Displacement	414	bbl	8.33			8	
Cement Left In Pipe		Amount	NONE			Reason		Shoe Joint	
Mix Water:		pH 7	Mix Water Chloride: <300 ppm			Mix Water Temperature: 61 °F			
Cement Temperature:		N/A	Plug Displaced by: 8.33 lb/gal F.W.			Disp. Temperature: 58 °F			
Plug Bumped?:		Yes	Bump Pressure: 2400 psi			Floats Held? Yes			
Cement Returns:		54 bbl	Returns Density: N/A			Returns Temperature: N/A			
<p>PUMPED CALCULATED DISPLACEMENT, PLUS 5 BBL WET SHOE, PLUG DID NOT LAND, RELEASED PRESSURE FLOATS DID NOT HOLD. BLED BACK 7 BBL AND TRIED PUMPING BACK IN 6 TIMES TO SEE IF FLOATS WOULD HOLD, FLOW RATE OF RETURNS DECREASED AFTER EACH ATEMPT. FLOATS NEVER DID HOLD, SHUT WELL IN AT MANIFOLD WITH PRESSURE GAUGE. HES RECOMMENDED TO HOLD PRESSURE ON WELL FOR 8 HRS.54 BBL CEMENT TO SURFACE</p>									

2.0 Real-Time Job Summary


2.1 Job Event Log

Type	Seq. No.	Activity	Graph Label	Date	Time	Source	DH Density (ppg)	Comb Pump Rate (bbl/min)	DS Pump Press (psi)	Comments
Event	1	Call Out	Call Out	5/14/2019	15:00:00	USER				CREW CALLED OUT AT 15:00 5/14/2019, REQUESTED ON LOCATION 23:00 5/14/2019. CREW PICKED UP CEMENT, CHEMICALS (25 GAL D-AIR, 1538 GAL FDP LATEX, 10 GAL MMCR), 100 LBS SUGAR, AND PLUG CONTAINER FROM FORT LUPTON, CO. BULK 660: 11645217/11633846 Bulk 660: 12644881 SOFT SIDE: 12240040/12051660 PUMP ELITE: 11897034/11645460.
Event	2	Pre-Convoy Safety Meeting	Pre-Convoy Safety Meeting	5/14/2019	21:45:00	USER				DISCUSSED ROUTES, HAZARDS, AND COMMUNICATION WITH CREW
Event	3	Crew Leave Yard	Crew Leave Yard	5/14/2019	22:00:00	USER				STARTED JOURNEY MANAGEMENT.
Event	4	Arrive At Loc	Arrive At Loc	5/14/2019	23:00:00	USER				END JOURNEY MANAGEMENT. MEET WITH CO. MAN TO DISCUSS JOB; SURFACE CASING: 9.625" 36# @ 1652', CASING: 5.5" 17# @ 18705', 5' SHOE JOINT, 8.5" OPEN HOLE, TVD @ 8045', 10 PPG WELL FLUID, FRESH WATER DISPLACEMENT.
Event	5	Pre-Rig Up Safety Meeting	Pre-Rig Up Safety Meeting	5/14/2019	23:10:00	USER				HAZARD HUNT. DISCUSSED POSSIBLE HAZARDS ASSOCIATED WITH LOCATION, RIG UP AND WEATHER.
Event	6	Rig-Up Equipment	Rig-Up Equipment	5/14/2019	23:20:00	USER				CREW STAGED EQUIPMENT AND RIGGED UP BULK, IRON, AND WATER HOSES TO PERFORM JOB.
Event	7	Pre-Job Safety Meeting	Pre-Job Safety Meeting	5/15/2019	06:45:00	USER	0.00	0.00	-3.00	MEETING WITH HALLIBURTON AND RIG PERSONNEL. COMMUNICATED POTENTIAL SAFETY HAZARDS AND JOB DETAILS.
Event	8	Start Job	Start Job	5/15/2019	07:19:48	COM4	0.00	0.00	-3.00	START JOB DATA RECORDING.
Event	9	Test Lines	Test Lines	5/15/2019	07:22:06	COM4	0.00	0.00	120.00	PRESSURE TESTED LINES TO 4900 PSI, 500 PSI KICK OUT AT 900 PSI, 5TH GEAR STALL AT 1870 PSI.

Event	10	Pump Spacer 1	Pump Spacer 1	5/15/2019	07:27:10	COM4	0.00	0.00	16.00	PUMP 50 BBLS OF FDP SPACER @ 12.5 LB/GAL, ADDED 10 GAL D-AIR, DENSITY VERIFIED BY PRESSURIZED MUD SCALES.
Event	11	Pump Cement	Pump Cap Cement	5/15/2019	07:38:25	COM4	12.58	5.70	181.00	PUMP 585 SKS OF ELASTICEM @ 13.2 LB/GAL, 1.6 YIELD, 7.75 GAL/SK, 166.7 BBLS, CALCULATED TOC @ SURFACE, DENSITY VERIFIED BY PRESSURIZED MUD SCALES.
Event	12	Pump Lead Cement	Pump Lead Cement	5/15/2019	08:00:48	COM4	13.16	8.30	517.00	PUMP 615 SKS OF GASSTOP @ 13.2 LB/GAL, 1.6 YIELD, 7.7 GAL/SK, 175.3 BBLS, CALCULATED TOL 2464', MIX WATER MIXED WITH 1538 GAL OF LATEX AND 20 GAL D-AIR, DENSITY VERIFIED BY PRESSURIZED MUD SCALES.
Event	13	Other	Mechacnical Trouble	5/15/2019	08:15:31	USER	13.24	8.30	560.00	FLECS SHUT DOWN TO LOW BATTERY VOLTAGE. 10 VOLTS. SHUTDOWN, HOOKED PICK UP BATTERY TO FLECS BATTERY VIA JUMPER CABLES, RESTARTED FLECS, RESUMED PUMPING JOB.
Event	14	Pre-Rig Down Safety Meeting	Pre-Rig Down Safety Meeting	5/15/2019	11:00:00	USER				DISCUSSED POSSIBLE HAZARDS ASSOCIATED WITH WEATHER, LOCATION AND RIGGING DOWN IRON AND HOSES.
Event	15	Rig-Down Completed	Rig-Down Completed	5/15/2019	13:00:00	USER				ALL HALLIBURTON ITEMS WERE STOWED FOR TRAVEL.
Event	16	Pre-Convoy Safety Meeting	Pre-Convoy Safety Meeting	5/15/2019	13:20:00	USER				DISCUSSED ROUTES HAZARDS AND COMMUNICATION WITH CREW.
Event	17	Crew Leave Location	Crew Leave Location	5/15/2019	13:30:00	USER				THANK YOU FOR USING HALLIBURTON - THOMAS HAAS AND CREW.

3.0 Attachments

3.1 Interchange B N35-20-5C Production – Start of Job Chart



3.2 End of Job Chart

