

DRILLERS' LOG

Hoffman No. 1
Loc: C SE NW
Sec: 26-25S-45W



Comm: 6-27-58
Comp: 7-18-58
Rotary Total Depth: 5300'
Casing: 8 5/8" at 558'
D & A.

Prowers County, Colorado
Company: Honaker-Davis Drlg. Co., et al
Contractor: Honaker-Davis Drlg. Co.

0	35	Top Soil
35	410	Blue Shale
410	505	Sand & Gravel
505	560	Shale & Pyrite
560	615	Iron
615	650	Gyp
650	790	Gyp & Sand
790	850	Sand
850	1210	Red Bed & Shale
1210	1490	Broken Gyp & Shale
1490	1600	Gyp
1600	1645	Gyp & Shale
1645	1805	Red Bed & Shale
1805	2005	Shale & Anhydrite
2005	3025	Lime & Shale
3025	3116	Lime
3116	3422	Lime & Shale
3422	4490	Lime
4490	4555	Lime & Shale
4555	4650	Lime
4650	5159	Lime & Shale
5159	5300	Lime
5300		Total Rotary Depth

8 5/8" casing cemented at
558' with 275 sacks common
cement and 2% calcium
chloride.



D & A

I certify that this is the true and correct copy of the
abovelog to the best of my knowledge.

H. S. Forbes

Subscribed and sworn to before me this 22nd day of
July, 1958.

Kenneth G. Fischer, Notary Public

My commission expires: 6-25-59

BEST IMAGE
AVAILABLE