


OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADOBEST IMAGE
AVAILABLE

PLUGGING RECORD

OIL & GAS
CONSERVATION COMMISSION

00938670

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator Vaughey & Vaughey Field Wildcat X
 Lease Name W. S. Sidney Well No. 1 County Otero
 Location SW/NE (Quarter Quarter) Section 3 Township 24S Range 59W Meridian 6
1980 feet from N Section line and 1980 feet from E Section Line
N or S E or W

TOTAL DEPTH 6573DATE OF PLUGGING August 22, 1957

DETAILS OF WORK

- Well was spudded June 29, 1957
- 315' 103/4" H-40 32.75# ST&C surface casing was set at 330' and cemented to surface with 275 sx regular cement with 2% CaCl₂.
- 8 3/4" hole was drilled to total depth.
- Well was plugged August 23, 1957, with regular cement placed as follows:
 20 sx at 6370-6420, 20 sx 1010-1060, 20 sx 300-350, 10 sx surface to 20'.
 Steel plate welded over surface pipe 2' below ground level. Mud between plugs weighed 9.8#/gallon. Schlumberger tops:

Fountain 3659'
 Morrow 5954'
 Mississippian 6312'
 Arbuckle 6419'
 Granite 6567'

AJJ	
DVR	
FJK	
OPS	
HHM	
AH	
JJD	<input checked="" type="checkbox"/>
FILE	

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date AUG 29 1957

Director

Company Vaughey & VaugheyDate Aug. 29, 1957Address 1650 Denver Club Bldg.Phone No. TA 5-8178

By

R. L. Hoss (Signature)Title Engineer