

HALLIBURTON

iCem[®] Service

EXTRACTION OIL & GAS

Date: Monday, May 20, 2019

AD FED LIBRARY 20W-25-18 Surface

Job Date: Saturday, April 27, 2019

Sincerely,

Bryce Hinsch

Legal Notice

Disclaimer:

All information in this report is provided subject to the terms and conditions which govern the services provided by Halliburton. Halliburton personnel use their best efforts in gathering information and their best judgment in interpreting it, but any interpretation, research, analysis or recommendation furnished by Halliburton are opinions based upon inferences from measurements and empirical relationships and assumptions, which inferences and empirical relationships and assumptions are not infallible, and with respect to which professionals in the industry may differ. iCem 3D Displacement results are used to understand how fluids intermix during a cement job. Simulation and 3D displacement results are not intended as and should not be used as a replacement for bond logs in determining top of cement. Current 3D model calculations are known to model more volume than the input volume for standard cases due to known calculation improvements required. For rotational cases, the modeled volume will be impacted by the same calculations impacting the standard cases, as well as additional constraints imposed to make the calculation time required operationally feasible. Therefore, until further notice, 3D displacement results should not be used for replacement of a bond log, or used as an identifier of top of cement. HALLIBURTON IS UNABLE TO GUARANTEE THE ACCURACY OF ANY CHART INTERPRETATION, RESEARCH ANALYSIS, OR JOB RECOMMENDATION and any interpretation or recommendation is not for use of or reliance upon by any third party. The customer has full responsibility for any of its decisions which are based on the information provided in this report.

Table of Contents

1.0 Cementing Job Summary 4

 1.1 Executive Summary4

2.0 Real-Time Job Summary 7

 2.1 Job Event Log7

3.0 Attachments..... 9

 3.1 Extraction AD FED LIBRARY 20W-25-18 Surface Chart.....9

1.0 Cementing Job Summary

1.1 Executive Summary

Halliburton appreciates the opportunity to perform the cementing services on the **AD FED Library 20W-25-18** cement **surface** casing job. A pre-job safety meeting was held before the job where details of the job were discussed, potential safety hazards were reviewed, and environmental compliance procedures were outlined.

Approximately 16 bbls of cement were returned to surface.

Halliburton maintains a continuous quality improvement process and appreciates any comments or suggestions that you may have. Halliburton again thanks you for the opportunity to perform service work on this well. We hope to be your solutions provider for future projects.

Respectfully,

Halliburton Fort Lupton

The Road to Excellence Starts with Safety

Sold To #: 369404		Ship To #: 3809178		Quote #:		Sales Order #: 0905639513					
Customer: EXTRACTION OIL & GAS -				Customer Rep: JUSTIN HUMPHRIES							
Well Name: AD FED LIBRARY			Well #: 20W-25-18		API/UWI #: 05-123-45037-00						
Field: WATTENBERG		City (SAP): GREELEY		County/Parish: WELD		State: COLORADO					
Legal Description: NW SW-21-5N-65W-1828FSL-367FWL											
Contractor:				Rig/Platform Name/Num: Cartel 15							
Job BOM: 7521 7521											
Well Type: HORIZONTAL OIL											
Sales Person: HALAMERICA\HX38199				Srv Supervisor: Jerald Watson							
Job											
Formation Name											
Formation Depth (MD)		Top		Bottom							
Form Type		BHST									
Job depth MD		1619ft		Job Depth TVD		1619					
Water Depth				Wk Ht Above Floor		0					
Perforation Depth (MD)		From		To							
Well Data											
Description	New / Used	Size in	ID in	Weight lbm/ft	Thread	Grade	Top MD ft	Bottom MD ft	Top TVD ft	Bottom TVD ft	
Open Hole Section			13.5				0	1620			
Casing		9.625	8.921	36			0	1619			
Tools and Accessories											
Type	Size in	Qty	Make	Depth ft		Type	Size in	Qty	Make		
Guide Shoe	9.625					Top Plug	9.625	1	HES		
Float Shoe	9.625	1	HES	1619		Bottom Plug	9.625		HES		
Float Collar	9.625	1	HES	1576		SSR plug set	9.625		HES		
Insert Float	9.625					Plug Container	9.625	1	HES		
Stage Tool	9.625					Centralizers	9.625	4	HES		
Fluid Data											
Stage/Plug #: 1											
Fluid #	Stage Type	Fluid Name			Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
1	Red Dye Spacer	Red Dye Spacer			10	bbl	8.33			4	

Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
2	SwiftCem	SWIFTCEM (TM) SYSTEM	515	sack	13.5	1.74		8	9.2
9.20 Gal		FRESH WATER							
Fluid #	Stage Type	Fluid Name	Qty	Qty UoM	Mixing Density lbm/gal	Yield ft3/sack	Mix Fluid Gal	Rate bbl/min	Total Mix Fluid Gal
3	Fresh Water	Fresh Water	122	bbl	8.33			8	
Cement Left In Pipe		Amount	43 ft		Reason			Shoe Joint	

2.0 Real-Time Job Summary

2.1 Job Event Log

Type	Seq. No.	Activity	Graph Label	Date	Time	Source	Comb Pump Rate (bbl/min)	DH Density (ppg)	DS Pump Press (psi)	Pump Stg Tot (bbl)	Comments
Event	1	Arrive at Location from Other Job or Site	Arrive at Location from Other Job or Site	4/26/2019	19:30:00	USER					REQUESTED ON LOC TIME 22:00, RIG PULLING DRILL PIPE UPON ARRIVAL
Event	2	Assessment Of Location Safety Meeting	Assessment Of Location Safety Meeting	4/26/2019	19:45:00	USER					TEST WATER, CHECK MATERIALS, GET NUMBERS FROM THE COMPANY MAN AND TALK ABOUT SPOTTING EQUIPMENT.
Event	3	Safety Meeting - Pre Rig-Up	Safety Meeting - Pre Rig-Up	4/26/2019	21:30:00	USER					DISCUSS HAZARDS ASSOCIATED WITH TASK
Event	4	Rig-Up Equipment	Rig-Up Equipment	4/26/2019	21:45:00	USER					RIG UP ALL EQUIPMENT
Event	5	Pre-Job Safety Meeting	Pre-Job Safety Meeting	4/27/2019	02:30:00	USER	0.10	8.33	-7.00	21.50	DISCUSS HAZARDS ASSOCIATED WITH THE JOB WITH EVERYONE INVOLVED WITH THE JOB AS WELL AS WHAT NEEDS TO BE DONE IN CASE OF EMERGENCY OR IF WE NEED TO EVACUATE LOCATION.
Event	6	Test Lines	Test Lines	4/27/2019	02:56:38	COM4	0.10	8.44	0.00	2.00	FILLED LINES, TESTED KICKOUTS TO 500 PSI, TESTED LINES TO 2500 PSI
Event	7	Pump Spacer 1	Pump Spacer 1	4/27/2019	02:58:27	COM4	0.80	8.40	3.00	0.00	10 BBL RED DYE H2O, 2 BPM, 20 PSI, 8.33 PPG
Event	8	Pump Cement	Pump Cement	4/27/2019	03:04:05	COM4	5.90	13.94	142.00	12.70	160 BBL SWIFTCM, 8 BPM, 245 PSI, 13.5 PPG
Event	9	Drop Top Plug	Drop Top Plug	4/27/2019	03:27:15	COM4	0.00	17.96	-4.00	161.10	HES TOP PLUG
Event	10	Pump Displacement	Pump Displacement	4/27/2019	03:27:24	COM4	0.00	17.96	-4.00	0.00	122 BBL H2O, 8 BPM, 485

											PSI, 8.33 PPG, 16 BBL CEMENT TO SURFACE
Event	11	Bump Plug	Bump Plug	4/27/2019	03:48:55	COM4	0.10	8.41	1010.00	124.20	BUMP PLUG AT 500 PSI, TOOK TO 1131 PSI
Event	12	Other	Other	4/27/2019	03:50:37	COM4	0.10	8.44	1134.00	124.40	1 BBL BACK
Event	13	Post-Job Safety Meeting (Pre Rig-Down)	Post-Job Safety Meeting (Pre Rig-Down)	4/27/2019	04:00:00	USER					DISCUSS HAZARDS INVOLVED AND IF ANYTHING IS STAYING ON LOCATION
Event	14	Rig-Down Equipment	Rig-Down Equipment	4/27/2019	04:15:00	USER					RIG DOWN ALL EQUIPMENT
Event	15	Pre-Convoy Safety Meeting	Pre-Convoy Safety Meeting	4/27/2019	04:45:00	USER					CHECK WITH EVERYONE TO SEE IF THEY ARE FIT TO DRIVE AND LEGAL TO DRIVE AND SEE WHAT THEIR PLANS ARE AS WELL AS DISCUSS ANY OTHER JOB THAT MAY NEED TO BE COVERED AFTER LEAVING LOCATION.
Event	16	Crew Leave Location	Crew Leave Location	4/27/2019	05:00:00	USER					EVERYONE LEAVES LOCATION

3.0 Attachments

3.1 Extraction AD FED LIBRARY 20W-25-18 Surface Chart

