

FORM
5A

Rev
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

402171540

Date Received:

09/10/2019

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 69175

2. Name of Operator: PDC ENERGY INC

3. Address: 1775 SHERMAN STREET - STE 3000

City: DENVER State: CO Zip: 80203

4. Contact Name: Cassie Gonzalez

Phone: (303) 860-5800

Fax:

Email: Cassie.Gonzalez@pdce.com

5. API Number 05-123-45259-00

7. Well Name: Thistle Down

8. Location: QtrQtr: NESW Section: 31 Township: 5N Range: 64W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 31H-332

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 07/06/2019 End Date: 07/14/2019 Date of First Production this formation: 08/19/2019
Perforations Top: 7309 Bottom: 12943 No. Holes: 1116 Hole size: 42/100

Provide a brief summary of the formation treatment:

Open Hole: ☐

32 Stage Plug and Perf
Total Fluid: 109,595 bbls
Gel Fluid: 71,773 bbls
Slickwater Fluid: 36,986 bbls
15% HCl Acid: 836 bbls
Total Proppant: 6,017,040 lbs
Silica Proppant: 6,017,040 lbs
Method for determining flowback: measuring flowback tank volumes.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 109595

Max pressure during treatment (psi): 4613

Total gas used in treatment (mcf):

Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment:

Min frac gradient (psi/ft): 0.99

Total acid used in treatment (bbl): 836

Number of staged intervals: 32

Recycled water used in treatment (bbl):

Flowback volume recovered (bbl): 3447

Fresh water used in treatment (bbl): 108759

Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 6017040

Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 08/23/2019 Hours: 24 Bbl oil: 312 Mcf Gas: 1226 Bbl H2O: 182
Calculated 24 hour rate: Bbl oil: 312 Mcf Gas: 1226 Bbl H2O: 182 GOR: 3929
Test Method: Flowing Casing PSI: 2697 Tubing PSI: 1794 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1302 API Gravity Oil: 53
Tubing Size: 2 + 3/8 Tubing Setting Depth: 7202 Tbg setting date: 07/30/2019 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

EP footages calculated by Lat 40: 760' FSL & 457' FWL Sec: 31 Twp: 5N Rng: 64W

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Cassie Gonzalez

Title: Regulatory Technician Date: 9/10/2019 Email: Cassie.Gonzalez@pdce.com

Attachment Check List

Att Doc Num Name

402171540 FORM 5A SUBMITTED

Total Attach: 1 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Passed Completion review.	09/13/2019

Total: 1 comment(s)