



SRC ENERGY

## P&A Wellbore Diagram

Operator: SRC Energy

Operator #: 10311

Well Name: ADAMS #1-25

Location: WELD #123

API: 05-123-11499

Legal: NENE 25 6N 66W

### Current

### Proposed

Deepest Water Well (1 mile): 331'

#### Well History

Spud Date: 11/22/1983

Perfs: Codell: 7166' - 7173'

#### Bradenhead History

Date of last test: N/A

Bradenhead pressure: N/A

#### Plugging Procedure

Set CIBP at 7091' MD

Run CBL

Spot 35 sc cement on top

Perf 4-1/2" csg at 2500' MD

Set CICR @ 2400'

Pump 84 sx through CICR

Set 9 sx on top of CICR (100' plug)

Cut casing at 927' MD

Pump 320 sx @ 977' to surface

#### Formations

Fox Hills (Btm)	827'
Upper Pierre (Top)	1422'
Sussex (Top)	4280'
Shannon (Top)	4880'
Niobrara (Top)	6896'
Codell (Top)	7160'

#### Legend

	Existing Cement
	Cement Pumped
	CIBP
	CICR

Surface Hole: 13.25"

Surface Casing:

9.625" 32# @ 315'

275 sacks of cement

TOC: 6657'

7166' - 7173'

Production Hole: 7.875"

Production Casing:

4.5" 11.6# @ 7257'

175 sacks of cement

TD: 7258'

927 Casing Cut

977 Stub Plug

(385' annular plug)

TOC: 2280'

(120' plug on CICR)

2400' - CICR

2500' - Perfs

TOC: 6631'

(460' plug)

35 sx on top

7091 CIBP