



# Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18<sup>th</sup> Street  
Denver, CO 80202  
720-929-6000

October 24, 2019

Jeff Robbins  
Director, Colorado Oil and Gas Conservation Commission  
Department of Natural Resources - The Chancery Building  
1120 Lincoln Street, Suite 801  
Denver, CO 80203

Re: **Request for Exception to Rule 317.p**

WINDSOCK 21-1HZ (Doc No. 402011489)  
WINDSOCK 21-2HZ (Doc No. 402011492)  
WINDSOCK 21-3HZ (Doc No. 402011493)  
WINDSOCK 21-4HZ (Doc No. 402011494)  
WINDSOCK 21-5HZ (Doc No. 402011495)  
WINDSOCK 21-6HZ (Doc No. 402011497)  
WINDSOCK 21-7HZ (Doc No. 402011498)  
WINDSOCK 21-8HZ (Doc No. 402011499)  
WINDSOCK 21-9HZ (Doc No. 402011500)  
WINDSOCK 21-10HZ (Doc No. 402011501)  
WINDSOCK 21-11HZ (Doc No. 402011502)

Township 1 North, Range 68 West  
Section 21: SWSE  
Weld County, CO

Dear Director Robbins:

Kerr-McGee Oil & Gas Onshore LP ("KMG") respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A cement bond log with cased-hole gamma ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well surface hole distance and bearing requirements.

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the

kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within fifteen hundred (1500) feet with acceptable resistivity logs with gamma ray are listed in the table below:

Well Name	Well Number	API Number	Distance From Well(s)	Azimuth (Degrees)	COGCC Well File Document Number
DUMP UU	28-2	05-123-25679	797'	148° SSE	1372511
CHAMPLIN 86 AMOCO UNIT L	1	05-123-12613	1484'	295° NW	1000416

Should you have any questions, please contact our office. Thank you for your consideration.

Respectfully,

**Kerr-McGee Oil and Gas Onshore LP**

A handwritten signature in black ink, appearing to be 'EH' or similar initials, written in a cursive style.

Erin Hampe  
Regulatory Analyst