

NOV 21 1957

OIL & GAS
CONSERVATION COMMISSION



00213366

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

SUNDRY NOTICES AND REPORTS ON WELLS

INSTRUCTIONS

Notice must be given to the Director, and approval obtained in advance of the time when the owner or operator expects to recompleate or abandon a well or to change plans. Within thirty (30) days after recompleation, change of plans, or remedial work, a detailed report of the work done and the results obtained shall be submitted on this form in duplicate for wells on Patented and Federal lands, and in triplicate for wells on State lands. In work that affects only rods, pumps or tubing or other routine work such as, but not limited to, cleaning out to previous total depth, no report is necessary.

Notice of Intention to Recomplete	<input type="checkbox"/>	Report of Remedial Work	<input type="checkbox"/>
Notice of Intention to Change Plans	<input type="checkbox"/>	Report of Recompletion	<input checked="" type="checkbox"/>
Notice of Intention to Abandon Well	<input type="checkbox"/>	Other	<input type="checkbox"/>

(Check appropriate space)

LEASE NAME Charles Kowach WELL NO. 1

FIELD Buck Peak WILDCAT COUNTY Moffat

LOCATION C NW NW Section 25 Township 6N Range 90W Meridian 6th P.M.

682 feet from North Section Line and 672 feet from West Section Line

N or S E or W

(DETAILS OF WORK)

Abandoned Entrada perforations 8820-8840'. Made 2 barrels salt water/hour.

Nov. 6, 1957: Set Baker cast iron bridge plug in 7" casing at 8700'.

Nov. 7, 1957: Ran tubing and retrievable production packer. Perforated with 4 Lane Wells swing jet shots per foot 8630-8650' in Morrison.

Nov. 8, 1957: Acidized with 250 gallons Halliburton mud acid, swabbed 2 barrels mud and water cut oil and 22.5 barrels water. Last 2 pulls scum of oil only.

November 11, 1957: Set Baker cast iron bridge plug in 7" casing at 6847'. Dumped 2 sacks 120 minute Calseal with bailer 6837-6847'.

Nov. 12, 1957: Perforated lower Tow Creek (Niobrara) with 2 jets and 2 bullets per foot 6760-6780', 6670-6740', 6620-6650' and perforated with 4 bullets per foot 6600-6620'. Pumped in 200 barrels crude oil at 2,000 psig.

Nov. 13, 1957: Swabbing back, will sand frac later.

AJJ	
DVR	
FJK	
WRS	
HHH	
AH	
FILE	

I/We hereby swear (or affirm) that the statements herein made are a full and correct report.

APPROVED:

NOV 21 1957

Date affirming WRS

Director

Company Malco Refineries, Inc. Date 11-14-57

Address P. O. Box 687 Craig, Colo. Phone No. TA4-5716

By H. T. Dean Title Dist. Prod. Supt.

(Signature)