

Enerplus Resources (USA) Corporation

**Weld County, CO
SEC 34 T8N-R66W
Polaris 8-66-34-33C**

Original Wellbore

Plan: Plan 3

Standard Planning Report

06 December, 2019

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Project	Weld County, CO		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		

Site		SEC 34 T8N-R66W			
Site Position:		Northing:	1,466,670.78 usft	Latitude:	40° 36' 43.362 N
From:	Lat/Long	Easting:	3,205,908.72 usft	Longitude:	104° 45' 30.060 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.48 °

Well	Polaris 8-66-34-33C					
Well Position	+N/-S	192.7 usft	Northing:	1,466,864.54 usft	Latitude:	40° 36' 45.266 N
	+E/-W	126.0 usft	Easting:	3,206,033.15 usft	Longitude:	104° 45' 28.426 W
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	4,996.0 usft

Wellbore	Original Wellbore				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	11/30/2019	7.96	66.96	52,221.07280800

Design	Plan 3			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	279.51

Plan Survey Tool Program	Date	12/6/2019			
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.0	17,485.3	Plan 3 (Original Wellbore)	MWD	
			OWSG MWD - Standard		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
3,600.7	24.01	36.59	3,554.2	265.4	197.0	1.50	1.50	0.00	36.59	
7,122.9	24.01	36.59	6,771.7	1,416.1	1,051.3	0.00	0.00	0.00	0.00	
8,182.7	90.00	264.02	7,466.0	1,585.2	479.8	10.00	6.23	-12.51	230.00	
8,361.6	90.00	269.39	7,466.0	1,574.9	301.2	3.00	0.00	3.00	90.00	
17,485.3	90.00	269.39	7,466.0	1,477.4	-8,821.9	0.00	0.00	0.00	0.00	Polaris 8-66-34-33C E

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
9-5/8" - Surface									
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
Begin 1.5° Nudge									
2,100.0	1.50	36.59	2,100.0	1.1	0.8	-0.6	1.50	1.50	0.00
2,200.0	3.00	36.59	2,199.9	4.2	3.1	-2.4	1.50	1.50	0.00
2,300.0	4.50	36.59	2,299.7	9.5	7.0	-5.4	1.50	1.50	0.00
2,400.0	6.00	36.59	2,399.3	16.8	12.5	-9.5	1.50	1.50	0.00
2,500.0	7.50	36.59	2,498.6	26.2	19.5	-14.9	1.50	1.50	0.00
2,600.0	9.00	36.59	2,597.5	37.8	28.0	-21.4	1.50	1.50	0.00
2,700.0	10.50	36.59	2,696.1	51.4	38.1	-29.1	1.50	1.50	0.00
2,800.0	12.00	36.59	2,794.2	67.0	49.8	-38.0	1.50	1.50	0.00
2,900.0	13.50	36.59	2,891.7	84.7	62.9	-48.1	1.50	1.50	0.00
3,000.0	15.00	36.59	2,988.6	104.5	77.6	-59.3	1.50	1.50	0.00
3,100.0	16.50	36.59	3,084.9	126.3	93.8	-71.6	1.50	1.50	0.00
3,200.0	18.00	36.59	3,180.4	150.1	111.4	-85.1	1.50	1.50	0.00
3,300.0	19.50	36.59	3,275.0	175.9	130.6	-99.8	1.50	1.50	0.00
3,400.0	21.00	36.59	3,368.9	203.7	151.2	-115.5	1.50	1.50	0.00
3,500.0	22.50	36.59	3,461.7	233.5	173.3	-132.4	1.50	1.50	0.00
3,600.0	24.00	36.59	3,553.6	265.2	196.8	-150.4	1.50	1.50	0.00
3,600.7	24.01	36.59	3,554.3	265.4	197.0	-150.5	1.43	1.43	0.00
Begin 24.01° Tangent									
3,700.0	24.01	36.59	3,645.0	297.8	221.1	-168.9	0.00	0.00	0.00
3,800.0	24.01	36.59	3,736.3	330.5	245.4	-187.4	0.00	0.00	0.00
3,900.0	24.01	36.59	3,827.7	363.2	269.6	-205.9	0.00	0.00	0.00
4,000.0	24.01	36.59	3,919.0	395.8	293.9	-224.5	0.00	0.00	0.00
4,100.0	24.01	36.59	4,010.4	428.5	318.1	-243.0	0.00	0.00	0.00
4,200.0	24.01	36.59	4,101.7	461.2	342.4	-261.5	0.00	0.00	0.00
4,300.0	24.01	36.59	4,193.1	493.8	366.6	-280.0	0.00	0.00	0.00
4,400.0	24.01	36.59	4,284.4	526.5	390.9	-298.6	0.00	0.00	0.00
4,500.0	24.01	36.59	4,375.7	559.2	415.1	-317.1	0.00	0.00	0.00
4,600.0	24.01	36.59	4,467.1	591.9	439.4	-335.6	0.00	0.00	0.00
4,700.0	24.01	36.59	4,558.4	624.5	463.6	-354.1	0.00	0.00	0.00
4,800.0	24.01	36.59	4,649.8	657.2	487.9	-372.7	0.00	0.00	0.00

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
4,900.0	24.01	36.59	4,741.1	689.9	512.2	-391.2	0.00	0.00	0.00	
5,000.0	24.01	36.59	4,832.5	722.5	536.4	-409.7	0.00	0.00	0.00	
5,100.0	24.01	36.59	4,923.8	755.2	560.7	-428.2	0.00	0.00	0.00	
5,200.0	24.01	36.59	5,015.2	787.9	584.9	-446.8	0.00	0.00	0.00	
5,300.0	24.01	36.59	5,106.5	820.5	609.2	-465.3	0.00	0.00	0.00	
5,400.0	24.01	36.59	5,197.9	853.2	633.4	-483.8	0.00	0.00	0.00	
5,500.0	24.01	36.59	5,289.2	885.9	657.7	-502.3	0.00	0.00	0.00	
5,600.0	24.01	36.59	5,380.6	918.6	681.9	-520.9	0.00	0.00	0.00	
5,700.0	24.01	36.59	5,471.9	951.2	706.2	-539.4	0.00	0.00	0.00	
5,800.0	24.01	36.59	5,563.3	983.9	730.4	-557.9	0.00	0.00	0.00	
5,900.0	24.01	36.59	5,654.6	1,016.6	754.7	-576.4	0.00	0.00	0.00	
6,000.0	24.01	36.59	5,746.0	1,049.2	779.0	-595.0	0.00	0.00	0.00	
6,100.0	24.01	36.59	5,837.3	1,081.9	803.2	-613.5	0.00	0.00	0.00	
6,200.0	24.01	36.59	5,928.7	1,114.6	827.5	-632.0	0.00	0.00	0.00	
6,300.0	24.01	36.59	6,020.0	1,147.3	851.7	-650.5	0.00	0.00	0.00	
6,400.0	24.01	36.59	6,111.3	1,179.9	876.0	-669.1	0.00	0.00	0.00	
6,500.0	24.01	36.59	6,202.7	1,212.6	900.2	-687.6	0.00	0.00	0.00	
6,600.0	24.01	36.59	6,294.0	1,245.3	924.5	-706.1	0.00	0.00	0.00	
6,700.0	24.01	36.59	6,385.4	1,277.9	948.7	-724.6	0.00	0.00	0.00	
6,800.0	24.01	36.59	6,476.7	1,310.6	973.0	-743.2	0.00	0.00	0.00	
6,900.0	24.01	36.59	6,568.1	1,343.3	997.2	-761.7	0.00	0.00	0.00	
7,000.0	24.01	36.59	6,659.4	1,375.9	1,021.5	-780.2	0.00	0.00	0.00	
7,100.0	24.01	36.59	6,750.8	1,408.6	1,045.8	-798.7	0.00	0.00	0.00	
7,122.9	24.01	36.59	6,771.7	1,416.1	1,051.3	-803.0	0.00	0.00	0.00	
KOP - Start 10°/100' Build										
7,200.0	19.90	19.01	6,843.3	1,441.1	1,065.0	-812.3	10.00	-5.33	-22.80	
7,300.0	18.24	348.48	6,938.0	1,472.6	1,067.4	-809.5	10.00	-1.66	-30.54	
7,400.0	21.51	320.35	7,032.3	1,502.2	1,052.5	-790.0	10.00	3.27	-28.13	
7,500.0	28.04	302.04	7,123.1	1,528.8	1,020.8	-754.3	10.00	6.52	-18.30	
7,600.0	36.09	290.77	7,207.9	1,551.8	973.2	-703.6	10.00	8.05	-11.27	
7,700.0	44.84	283.28	7,283.9	1,570.4	911.2	-639.3	10.00	8.75	-7.49	
7,800.0	53.95	277.83	7,349.0	1,584.0	836.7	-563.6	10.00	9.11	-5.45	
7,900.0	63.26	273.53	7,401.0	1,592.3	751.8	-478.5	10.00	9.31	-4.30	
8,000.0	72.67	269.89	7,438.5	1,595.0	659.3	-386.8	10.00	9.42	-3.64	
8,100.0	82.15	266.61	7,460.3	1,592.0	561.9	-291.2	10.00	9.47	-3.28	
8,182.7	90.00	264.02	7,466.0	1,585.2	479.7	-211.3	10.00	9.50	-3.14	
7" - 2012' FSL & 623' FEL - Intermediate										
8,200.0	90.00	264.54	7,466.0	1,583.5	462.5	-194.6	3.00	0.00	3.00	
8,300.0	90.00	267.54	7,466.0	1,576.6	362.8	-97.4	3.00	0.00	3.00	
8,361.6	90.00	269.39	7,466.0	1,574.9	301.2	-36.9	3.00	0.00	3.00	
8,400.0	90.00	269.39	7,466.0	1,574.5	262.8	0.9	0.00	0.00	0.00	
8,500.0	90.00	269.39	7,466.0	1,573.5	162.8	99.3	0.00	0.00	0.00	
8,600.0	90.00	269.39	7,466.0	1,572.4	62.8	197.8	0.00	0.00	0.00	
8,700.0	90.00	269.39	7,466.0	1,571.3	-37.2	296.2	0.00	0.00	0.00	
8,800.0	90.00	269.39	7,466.0	1,570.3	-137.2	394.6	0.00	0.00	0.00	
8,900.0	90.00	269.39	7,466.0	1,569.2	-237.2	493.1	0.00	0.00	0.00	
9,000.0	90.00	269.39	7,466.0	1,568.1	-337.2	591.5	0.00	0.00	0.00	
9,100.0	90.00	269.39	7,466.0	1,567.1	-437.2	690.0	0.00	0.00	0.00	
9,200.0	90.00	269.39	7,466.0	1,566.0	-537.2	788.4	0.00	0.00	0.00	
9,300.0	90.00	269.39	7,466.0	1,564.9	-637.2	886.9	0.00	0.00	0.00	
9,400.0	90.00	269.39	7,466.0	1,563.8	-737.2	985.3	0.00	0.00	0.00	
9,500.0	90.00	269.39	7,466.0	1,562.8	-837.1	1,083.8	0.00	0.00	0.00	
9,600.0	90.00	269.39	7,466.0	1,561.7	-937.1	1,182.2	0.00	0.00	0.00	
9,700.0	90.00	269.39	7,466.0	1,560.6	-1,037.1	1,280.6	0.00	0.00	0.00	

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
9,800.0	90.00	269.39	7,466.0	1,559.6	-1,137.1	1,379.1	0.00	0.00	0.00	
9,900.0	90.00	269.39	7,466.0	1,558.5	-1,237.1	1,477.5	0.00	0.00	0.00	
10,000.0	90.00	269.39	7,466.0	1,557.4	-1,337.1	1,576.0	0.00	0.00	0.00	
10,100.0	90.00	269.39	7,466.0	1,556.4	-1,437.1	1,674.4	0.00	0.00	0.00	
10,200.0	90.00	269.39	7,466.0	1,555.3	-1,537.1	1,772.9	0.00	0.00	0.00	
10,300.0	90.00	269.39	7,466.0	1,554.2	-1,637.1	1,871.3	0.00	0.00	0.00	
10,400.0	90.00	269.39	7,466.0	1,553.2	-1,737.1	1,969.8	0.00	0.00	0.00	
10,500.0	90.00	269.39	7,466.0	1,552.1	-1,837.1	2,068.2	0.00	0.00	0.00	
10,600.0	90.00	269.39	7,466.0	1,551.0	-1,937.1	2,166.6	0.00	0.00	0.00	
10,700.0	90.00	269.39	7,466.0	1,550.0	-2,037.1	2,265.1	0.00	0.00	0.00	
10,800.0	90.00	269.39	7,466.0	1,548.9	-2,137.1	2,363.5	0.00	0.00	0.00	
10,900.0	90.00	269.39	7,466.0	1,547.8	-2,237.1	2,462.0	0.00	0.00	0.00	
11,000.0	90.00	269.39	7,466.0	1,546.7	-2,337.1	2,560.4	0.00	0.00	0.00	
11,100.0	90.00	269.39	7,466.0	1,545.7	-2,437.1	2,658.9	0.00	0.00	0.00	
11,200.0	90.00	269.39	7,466.0	1,544.6	-2,537.0	2,757.3	0.00	0.00	0.00	
11,300.0	90.00	269.39	7,466.0	1,543.5	-2,637.0	2,855.8	0.00	0.00	0.00	
11,400.0	90.00	269.39	7,466.0	1,542.5	-2,737.0	2,954.2	0.00	0.00	0.00	
11,500.0	90.00	269.39	7,466.0	1,541.4	-2,837.0	3,052.6	0.00	0.00	0.00	
11,600.0	90.00	269.39	7,466.0	1,540.3	-2,937.0	3,151.1	0.00	0.00	0.00	
11,700.0	90.00	269.39	7,466.0	1,539.3	-3,037.0	3,249.5	0.00	0.00	0.00	
11,800.0	90.00	269.39	7,466.0	1,538.2	-3,137.0	3,348.0	0.00	0.00	0.00	
11,900.0	90.00	269.39	7,466.0	1,537.1	-3,237.0	3,446.4	0.00	0.00	0.00	
12,000.0	90.00	269.39	7,466.0	1,536.1	-3,337.0	3,544.9	0.00	0.00	0.00	
12,100.0	90.00	269.39	7,466.0	1,535.0	-3,437.0	3,643.3	0.00	0.00	0.00	
12,200.0	90.00	269.39	7,466.0	1,533.9	-3,537.0	3,741.8	0.00	0.00	0.00	
12,300.0	90.00	269.39	7,466.0	1,532.9	-3,637.0	3,840.2	0.00	0.00	0.00	
12,400.0	90.00	269.39	7,466.0	1,531.8	-3,737.0	3,938.6	0.00	0.00	0.00	
12,500.0	90.00	269.39	7,466.0	1,530.7	-3,837.0	4,037.1	0.00	0.00	0.00	
12,600.0	90.00	269.39	7,466.0	1,529.6	-3,937.0	4,135.5	0.00	0.00	0.00	
12,700.0	90.00	269.39	7,466.0	1,528.6	-4,037.0	4,234.0	0.00	0.00	0.00	
12,800.0	90.00	269.39	7,466.0	1,527.5	-4,137.0	4,332.4	0.00	0.00	0.00	
12,900.0	90.00	269.39	7,466.0	1,526.4	-4,237.0	4,430.9	0.00	0.00	0.00	
13,000.0	90.00	269.39	7,466.0	1,525.4	-4,336.9	4,529.3	0.00	0.00	0.00	
13,100.0	90.00	269.39	7,466.0	1,524.3	-4,436.9	4,627.8	0.00	0.00	0.00	
13,200.0	90.00	269.39	7,466.0	1,523.2	-4,536.9	4,726.2	0.00	0.00	0.00	
13,300.0	90.00	269.39	7,466.0	1,522.2	-4,636.9	4,824.7	0.00	0.00	0.00	
13,400.0	90.00	269.39	7,466.0	1,521.1	-4,736.9	4,923.1	0.00	0.00	0.00	
13,500.0	90.00	269.39	7,466.0	1,520.0	-4,836.9	5,021.5	0.00	0.00	0.00	
13,600.0	90.00	269.39	7,466.0	1,519.0	-4,936.9	5,120.0	0.00	0.00	0.00	
13,700.0	90.00	269.39	7,466.0	1,517.9	-5,036.9	5,218.4	0.00	0.00	0.00	
13,800.0	90.00	269.39	7,466.0	1,516.8	-5,136.9	5,316.9	0.00	0.00	0.00	
13,900.0	90.00	269.39	7,466.0	1,515.8	-5,236.9	5,415.3	0.00	0.00	0.00	
14,000.0	90.00	269.39	7,466.0	1,514.7	-5,336.9	5,513.8	0.00	0.00	0.00	
14,100.0	90.00	269.39	7,466.0	1,513.6	-5,436.9	5,612.2	0.00	0.00	0.00	
14,200.0	90.00	269.39	7,466.0	1,512.5	-5,536.9	5,710.7	0.00	0.00	0.00	
14,300.0	90.00	269.39	7,466.0	1,511.5	-5,636.9	5,809.1	0.00	0.00	0.00	
14,400.0	90.00	269.39	7,466.0	1,510.4	-5,736.9	5,907.5	0.00	0.00	0.00	
14,500.0	90.00	269.39	7,466.0	1,509.3	-5,836.9	6,006.0	0.00	0.00	0.00	
14,600.0	90.00	269.39	7,466.0	1,508.3	-5,936.9	6,104.4	0.00	0.00	0.00	
14,700.0	90.00	269.39	7,466.0	1,507.2	-6,036.8	6,202.9	0.00	0.00	0.00	
14,800.0	90.00	269.39	7,466.0	1,506.1	-6,136.8	6,301.3	0.00	0.00	0.00	
14,900.0	90.00	269.39	7,466.0	1,505.1	-6,236.8	6,399.8	0.00	0.00	0.00	
15,000.0	90.00	269.39	7,466.0	1,504.0	-6,336.8	6,498.2	0.00	0.00	0.00	
15,100.0	90.00	269.39	7,466.0	1,502.9	-6,436.8	6,596.7	0.00	0.00	0.00	

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
15,200.0	90.00	269.39	7,466.0	1,501.9	-6,536.8	6,695.1	0.00	0.00	0.00	
15,300.0	90.00	269.39	7,466.0	1,500.8	-6,636.8	6,793.5	0.00	0.00	0.00	
15,400.0	90.00	269.39	7,466.0	1,499.7	-6,736.8	6,892.0	0.00	0.00	0.00	
15,500.0	90.00	269.39	7,466.0	1,498.7	-6,836.8	6,990.4	0.00	0.00	0.00	
15,600.0	90.00	269.39	7,466.0	1,497.6	-6,936.8	7,088.9	0.00	0.00	0.00	
15,700.0	90.00	269.39	7,466.0	1,496.5	-7,036.8	7,187.3	0.00	0.00	0.00	
15,800.0	90.00	269.39	7,466.0	1,495.4	-7,136.8	7,285.8	0.00	0.00	0.00	
15,900.0	90.00	269.39	7,466.0	1,494.4	-7,236.8	7,384.2	0.00	0.00	0.00	
16,000.0	90.00	269.39	7,466.0	1,493.3	-7,336.8	7,482.7	0.00	0.00	0.00	
16,100.0	90.00	269.39	7,466.0	1,492.2	-7,436.8	7,581.1	0.00	0.00	0.00	
16,200.0	90.00	269.39	7,466.0	1,491.2	-7,536.8	7,679.5	0.00	0.00	0.00	
16,300.0	90.00	269.39	7,466.0	1,490.1	-7,636.8	7,778.0	0.00	0.00	0.00	
16,400.0	90.00	269.39	7,466.0	1,489.0	-7,736.8	7,876.4	0.00	0.00	0.00	
16,500.0	90.00	269.39	7,466.0	1,488.0	-7,836.7	7,974.9	0.00	0.00	0.00	
16,600.0	90.00	269.39	7,466.0	1,486.9	-7,936.7	8,073.3	0.00	0.00	0.00	
16,700.0	90.00	269.39	7,466.0	1,485.8	-8,036.7	8,171.8	0.00	0.00	0.00	
16,800.0	90.00	269.39	7,466.0	1,484.8	-8,136.7	8,270.2	0.00	0.00	0.00	
16,900.0	90.00	269.39	7,466.0	1,483.7	-8,236.7	8,368.7	0.00	0.00	0.00	
17,000.0	90.00	269.39	7,466.0	1,482.6	-8,336.7	8,467.1	0.00	0.00	0.00	
17,100.0	90.00	269.39	7,466.0	1,481.6	-8,436.7	8,565.5	0.00	0.00	0.00	
17,200.0	90.00	269.39	7,466.0	1,480.5	-8,536.7	8,664.0	0.00	0.00	0.00	
17,300.0	90.00	269.39	7,466.0	1,479.4	-8,636.7	8,762.4	0.00	0.00	0.00	
17,400.0	90.00	269.39	7,466.0	1,478.3	-8,736.7	8,860.9	0.00	0.00	0.00	
17,485.3	90.00	269.39	7,466.0	1,477.4	-8,821.9	8,944.8	0.00	0.00	0.00	
PBHL										

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude		Longitude
- hit/miss target										
- Shape										
Polaris 8-66-34-33C BHI	0.00	0.00	7,466.0	1,477.4	-8,821.9	1,468,268.10	3,197,199.15	40° 36' 59.850 N		104° 47' 22.823 W
- plan hits target center										
- Point										
Polaris 8-66-34-33C LP	0.00	0.00	7,466.0	1,585.2	479.7	1,468,453.66	3,206,499.59	40° 37' 0.930 N		104° 45' 22.205 W
- plan misses target center by 0.1usft at 8182.7usft MD (7466.0 TVD, 1585.2 N, 479.7 E)										
- Point										

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")	
1,500.0	1,500.0	Surface	9-5/8	9-5/8	
8,182.7	7,466.0	Intermediate	7	7	

Planning Report

Database:	EDM Server Database	Local Co-ordinate Reference:	Well Polaris 8-66-34-33C
Company:	Enerplus Resources (USA) Corporation	TVD Reference:	KB @ 5012.0usft
Project:	Weld County, CO	MD Reference:	KB @ 5012.0usft
Site:	SEC 34 T8N-R66W	North Reference:	True
Well:	Polaris 8-66-34-33C	Survey Calculation Method:	Minimum Curvature
Wellbore:	Original Wellbore		
Design:	Plan 3		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
1,500.0	1,500.0	0.0	0.0	9-5/8"
2,000.0	2,000.0	0.0	0.0	Begin 1.5° Nudge
3,600.7	3,554.3	265.4	197.0	Begin 24.01° Tangent
7,122.9	6,771.7	1,416.1	1,051.3	KOP - Start 10°/100' Build
8,182.7	7,466.0	1,585.2	479.7	7" - 2012' FSL & 623' FEL
17,485.3	7,466.0	1,477.4	-8,821.9	PBHL