



SRC ENERGY

Operator: SRC Energy
Well Name: Monfort E 30-30
Legal: NWNW, Section 30, Township 6N, Range 65W
Location: Weld County, CO
API: 05-123-24932
Surface: 8.625" 24# @ 470' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7654' **Hole Size:** 7.875" **TOC:** 2,087' (CBL)
Perforations: 7,485' – 7,500' (Codell)
TD: 7,654'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 7,263'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 24 sx on top of CIBP
8. Cut 4.5" casing at 1500' and POOH
9. Pump balanced plug, 90 sx @ 1550'
10. TIH to 1040' and pump stub plug (0' – 1040')
 - a. 315 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 570' out of surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&R complete