



Job Number: SVGJ-170140 - API: 05-123-21408

Company: PDC

Lease/Well: Linkus 41-24

Location: Weld County, CO

Rig Name: N/A

RKB: 0'

G.L. or M.S.L.: GL

State/Country: Colorado/USA

Declination: 8.42°

Grid: East To True North

File name: C:\WINSER~1\2017\PDC\GJ\LINKUS\4124.SVY

Date/Time: 07-Nov-17 / 11:05

Curve Name: Surface - 8200' M.D. (Rate Gyro)

Lat: 40.042489 Long: -104.944685

MS Energy

WINSERVE SURVEY CALCULATIONS
 Minimum Curvature Method
 Vertical Section Plane .00
 Vertical Section Referenced to Wellhead
 Rectangular Coordinates Referenced to Wellhead

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
100.00	.47	319.19	100.00	.31	-.27	.31	.41	319.19	.47
200.00	.45	315.12	200.00	.90	-.81	.90	1.21	317.87	.04
300.00	.42	313.78	299.99	1.43	-1.35	1.43	1.97	316.56	.03
400.00	.41	319.16	399.99	1.96	-1.85	1.96	2.69	316.53	.04
500.00	.03	113.38	499.99	2.22	-2.06	2.22	3.03	317.04	.44
600.00	.17	166.94	599.99	2.06	-2.01	2.06	2.88	315.77	.15
700.00	.28	125.25	699.99	1.78	-1.77	1.78	2.51	315.04	.19
800.00	.25	100.26	799.99	1.60	-1.36	1.60	2.10	319.58	.12
900.00	.22	90.03	899.99	1.56	-.95	1.56	1.82	328.55	.05
1000.00	.19	104.69	999.99	1.51	-.60	1.51	1.63	338.40	.06
1100.00	.14	121.11	1099.99	1.41	-.33	1.41	1.45	346.64	.07
1200.00	.18	205.07	1199.99	1.20	-.30	1.20	1.24	346.16	.22

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
1300.00	.33	235.10	1299.98	.90	-.60	.90	1.08	326.24	.20
1400.00	.51	253.89	1399.98	.61	-1.26	.61	1.40	295.71	.22
1500.00	.64	265.99	1499.98	.45	-2.25	.45	2.29	281.22	.18
1600.00	.99	271.35	1599.97	.43	-3.67	.43	3.69	276.64	.36
1700.00	1.19	275.96	1699.95	.56	-5.56	.56	5.59	275.70	.22
1800.00	1.30	274.53	1799.92	.75	-7.73	.75	7.77	275.56	.11
1900.00	1.38	281.82	1899.90	1.09	-10.04	1.09	10.10	276.19	.19
2000.00	1.35	291.17	1999.87	1.76	-12.32	1.76	12.44	278.14	.22
2100.00	1.33	292.18	2099.84	2.62	-14.49	2.62	14.72	280.27	.03
2200.00	1.12	290.02	2199.82	3.40	-16.48	3.40	16.83	281.65	.21
2300.00	.96	289.23	2299.80	4.01	-18.19	4.01	18.63	282.42	.16
2400.00	.99	291.86	2399.79	4.61	-19.78	4.61	20.31	283.10	.05
2500.00	1.03	302.55	2499.77	5.41	-21.34	5.41	22.02	284.23	.19
2600.00	1.04	303.53	2599.76	6.40	-22.86	6.40	23.73	285.63	.02
2700.00	1.19	314.88	2699.74	7.63	-24.35	7.63	25.52	287.40	.27
2800.00	1.27	314.53	2799.71	9.14	-25.87	9.14	27.44	289.45	.08
2900.00	1.36	309.62	2899.69	10.67	-27.58	10.67	29.57	291.16	.14
3000.00	1.43	302.73	2999.66	12.10	-29.54	12.10	31.93	292.28	.18
3100.00	1.49	293.74	3099.63	13.30	-31.78	13.30	34.45	292.71	.24
3200.00	1.44	284.97	3199.59	14.15	-34.19	14.15	37.00	292.49	.23
3300.00	1.50	285.82	3299.56	14.83	-36.66	14.83	39.55	292.03	.06
3400.00	1.76	292.83	3399.52	15.78	-39.33	15.78	42.38	291.87	.33
3500.00	1.74	298.30	3499.47	17.10	-42.09	17.10	45.43	292.11	.17
3600.00	1.82	291.48	3599.43	18.40	-44.90	18.40	48.53	292.29	.23
3700.00	1.80	293.58	3699.38	19.61	-47.82	19.61	51.68	292.30	.07
3800.00	1.80	295.49	3799.33	20.92	-50.67	20.92	54.82	292.43	.06
3900.00	1.73	297.42	3899.28	22.29	-53.43	22.29	57.89	292.64	.09
4000.00	1.84	296.96	3999.23	23.71	-56.20	23.71	61.00	292.87	.11
4100.00	2.13	294.86	4099.17	25.22	-59.32	25.22	64.46	293.03	.30
4200.00	2.24	293.76	4199.10	26.79	-62.80	26.79	68.27	293.10	.12
4300.00	2.27	297.70	4299.02	28.50	-66.34	28.50	72.20	293.25	.16
4400.00	2.21	303.19	4398.94	30.47	-69.70	30.47	76.07	293.61	.22
4500.00	2.19	304.82	4498.87	32.62	-72.89	32.62	79.85	294.11	.07
4600.00	1.99	316.38	4598.80	34.97	-75.65	34.97	83.34	294.81	.47

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
4700.00	1.83	325.57	4698.75	37.54	-77.75	37.54	86.34	295.77	.35
4800.00	1.89	323.26	4798.70	40.18	-79.64	40.18	89.20	296.77	.10
4900.00	1.93	321.93	4898.64	42.83	-81.67	42.83	92.21	297.67	.06
5000.00	1.91	320.21	4998.58	45.43	-83.77	45.43	95.30	298.47	.06
5100.00	1.77	319.67	5098.53	47.89	-85.84	47.89	98.29	299.16	.14
5200.00	1.73	319.74	5198.49	50.22	-87.81	50.22	101.16	299.76	.04
5300.00	1.65	319.08	5298.44	52.46	-89.73	52.46	103.94	300.31	.08
5400.00	1.62	322.03	5398.40	54.66	-91.54	54.66	106.62	300.84	.09
5500.00	1.43	324.99	5498.37	56.80	-93.13	56.80	109.08	301.38	.21
5600.00	1.33	324.20	5598.34	58.76	-94.52	58.76	111.30	301.87	.10
5700.00	1.23	329.74	5698.31	60.63	-95.74	60.63	113.33	302.34	.16
5800.00	1.07	327.55	5798.29	62.34	-96.79	62.34	115.13	302.79	.17
5900.00	.95	330.94	5898.28	63.86	-97.69	63.86	116.71	303.17	.13
6000.00	.85	330.79	5998.26	65.23	-98.45	65.23	118.10	303.53	.10
6100.00	.71	339.30	6098.25	66.45	-99.04	66.45	119.27	303.86	.18
6200.00	.55	338.85	6198.25	67.48	-99.43	67.48	120.17	304.16	.16
6300.00	.48	3.13	6298.24	68.35	-99.58	68.35	120.78	304.46	.23
6400.00	.72	43.22	6398.24	69.22	-99.13	69.22	120.90	304.93	.47
6500.00	.66	33.82	6498.23	70.16	-98.37	70.16	120.83	305.50	.13
6600.00	.59	31.49	6598.23	71.08	-97.78	71.08	120.89	306.01	.07
6700.00	.52	28.72	6698.22	71.91	-97.30	71.91	120.99	306.47	.07
6800.00	.45	10.75	6798.22	72.70	-97.01	72.70	121.22	306.85	.17
6900.00	.66	4.63	6898.21	73.66	-96.89	73.66	121.71	307.24	.22
7000.00	.68	351.69	6998.21	74.82	-96.93	74.82	122.44	307.67	.15
7100.00	.86	12.45	7098.20	76.14	-96.85	76.14	123.20	308.17	.33
7200.00	.95	25.51	7198.19	77.62	-96.33	77.62	123.71	308.86	.22
7300.00	1.35	36.96	7298.17	79.31	-95.27	79.31	123.96	309.78	.46
7400.00	1.83	43.05	7398.13	81.42	-93.47	81.42	123.96	311.06	.51
7500.00	1.63	59.07	7498.08	83.32	-91.16	83.32	123.50	312.43	.52
7600.00	1.67	120.15	7598.05	83.32	-88.68	83.32	121.68	313.21	1.68
7700.00	2.17	134.91	7697.99	81.25	-86.08	81.25	118.36	313.35	.70
7800.00	2.17	131.07	7797.92	78.67	-83.31	78.67	114.58	313.36	.15
7900.00	2.39	124.07	7897.84	76.25	-80.15	76.25	110.63	313.57	.35
8000.00	2.04	126.08	7997.77	74.04	-76.99	74.04	106.81	313.88	.36

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E Distance FT	Direction Deg	Dogleg Severity Deg/100
8100.00	1.59	127.05	8097.72	72.15	-74.44	72.15	103.67	314.11	.45
Last Survey Depth Recorded									
8200.00	1.34	134.10	8197.68	70.50	-72.50	70.50	101.13	314.20	.31