



SRC ENERGY

Operator: SRC Energy
Well Name: Ikenouye F 29-23
Legal: NWSE, Section 29, Township 5N, Range 65W
Location: Weld County, CO
API: 05-123-25554
Surface: 8.625" 24# @ 530' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,654' **Hole Size:** 7.875" **TOC:** 1800' (CBL)
Perforations: 6,740'-6,882' (Nio); 7,048'-7,065' (Codell)
TD: 7,656'

Annular Fill Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. Set 11.6# CIBP @ 2000' with sand
6. Pressure test casing to 500 psi for 15 minutes.
7. Run CBL from 2000' to surface
8. TIH and perforate casing @ 1550'
9. TIH w/ 4-1/2" 11.6# packer, set at 1500'
 - a. Squeeze perfs w/ 60 sx (300' annulus plug)
 - b. Release packer and circulate clean
10. Allow cement at least 4 hrs to cure
11. Pressure test squeeze to 500 psi and run CBL from 2000' to surface confirming cement placement
12. Perform bradenhead test confirming no flow or pressure
13. Retrieve RBP and re-land tubing
14. RDMO WO unit
15. Annular fill complete