



## Partner Summary Report

Date: 3/20/2017

Report #: 1

Well Name: SPEICHER 41-15

DOL:

Spud Date: 3/9/2006

### Well Header

Well Name SPEICHER 41-15	API 05-123-23540	County/Parish WELD	State/Province COLORADO		Total Depth All (TVD) (ftKB)		Current PBTD (ftKB) ORIGINAL HOLE - 7,085.0		
Spud Date 3/9/2006		TD Date 3/13/2006		Rig Release Date 3/13/2006			First Gas Sales 5/31/2006		
Actual Latitude (°) 40.49158605		Actual Longitude (°) -104.52935357		Quarter 3 NE	Quarter 4 NE	Section 15	Township 6	Township N/S Dir N	Range E/W Dir W

Job: OTHER , Job Start Date: 3/20/2017 06:00

Objective WBI	AFE Number
------------------	------------

Report Start Date 3/20/2017 06:00	Report End Date 3/20/2017 20:00	Operations Summary ROAD RIG TO LOCATION. SPOT IN AND R/U RANGER #5. IWP = 0/0#. SURFACE CSG = 0#. WELL PREVIOUSLY BLOWN DOWN BY RPS FLOW BACK CREW TO 500 BBL OPEN TOP TANK. LOAD TBG AND CSG WITH 2% KCL WATER W/BIOCIDE. ESTABLISH REVERSE CIRCULATION. ROLL CLEAN. N/D WELLHEAD TREE. N/U BOP. TOOH AND TALLY WHILE S/B IN DERRICK 214 JTS 2 3/8" 4.7# J-55 EUE 8RD TBG IN DERRICK. L/D ON SILLS NC/SN. TIH OUT OF DERRICK WITH STS-RBP, XN-NIPPLE AND 214 JTS 2 3/8" 4.7# J-55 EUE 8RD TBG. SET RBP WITH 15K IN TENSION @ 6915.61' KB, (26.00' OUT ON JT 214). RELEASE ON/OFF TOOL. POOH L/D ON SILLS 1 JT TBG. LOAD TBG AND BACKSIDE WITH 2% KCL WATER W/BIOCIDE. ESTABLISH REVERSE CIRCULATION. ROLL CLEAN. PRESSURE TEST RBP/CSG @ 2500#, HELD 15/MIN. TEST GOOD. BLEED OFF. POOH L/D ON SILLS 19 JTS TBG, FOR TOTAL OF 20 JTS TBG ON SILLS. LAND TBG WITH RETRIEVING HEAD, XN-NIPPLE AND 194 JTS TBG @ 6293.06' KB. N/D BOP. STRIP OFF 3K WELLHEAD USING STS 4 1/2" TOAD STOOL ON SURFACE CSG HEAD, STRIP ON 5K WELLHEAD. FLANGE UP WELLHEAD. SPOT TWO SXS 20/40 SAND ONTO RBP, FOLLOWED WITH 2% KCL WATER W/BIO. SI WELL. RDMO.  AFE #203469
--------------------------------------	------------------------------------	--