

RECEIVED

JUN 04 1984

COLO. OIL & GAS CONS. COMM.

PLUGGING PROCEDURE

Teale 1-32
300' FWL & 500' FSL
Section 32-T7N-R86W
Routt County, Colorado
Trigg Drilling Company, Inc., Operator

Mechanicals

9-5/8" surface casing at 213'. Cement to surface. 5-1/2" casing at 2797', set with external casing packer. 2-3/8" tubing at 2500'. Open hole 2797' - 3980'.

Plugging Procedure

1. MIRU.
2. Fill hole with water, Set 100 foot (20 sack) cement plug across base of 5-1/2" casing. TOOH with tubing.
3. Set 10 sack surface plug. Cut off casing head below plow depth.
4. Reclaim location per Routt County Planning Commission specifications.



45

RECEIVED

MAY 9

COLORADO OIL & GAS

TRIGG DRILLING COMPANY, INC.
DAILY DRILLING REPORT
ROCKY MOUNTAIN REGION

WELL	DATE	REPORT
<u>Trigg Operated</u>		
TEALE 1-32 SW SW Sec. 32-T7N-R86W Routt County, CO AFE #580980	11/13/84	MIRU Prairie Gold Well Servicing WO rig, POOH 83 jts 2-3/8" tbg, RIH w/83 jts 2-3/8" tbg. SDFD
	11/14/84	PU 8 jts 2-3/8" tbg, tot 91 jts in hole, set @ 2808', cmt w/35 sxs Class A Neat, flush w/6 BW, LD 86 jts tbg, cmt w/10 sxs Class A Neat. LD remaining 5 jts tbg. RDMO.

Note: Did not cut off any wellheads because of
bad weather, and need to pickup junk pipe.

