

OIL AND GAS CONSERVATION COMMISSION
DEPARTMENT OF NATURAL RESOURCES
OF THE STATE OF COLORADO

RECEIVED

JUL 20 1979

File in duplicate for Patented and Federal lands
File in triplicate for State lands.

COLO. OIL & GAS CONS. COMM.

5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL GAS WELL OTHER Dry Hole

2. NAME OF OPERATOR
DIETRICH EXPLORATION COMPANY - THE BRINKERHOFF COMPANY

3. ADDRESS OF OPERATOR
602 Midland Savings Bldg.
Denver, CO 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 2004' FNL & 2017' FWL Section 11
At proposed prod. zone
Same

14. PERMIT NO. 79-479

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
6378' Gr.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Johnson

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
11-7N-90W

12. COUNTY Moffat

13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work July 4, 1979

Hole filled with heavy mud.
Set 25 sacks cement across base of surface casing at 309'.
Set 10 sacks cement in top of surface casing.
Welded cap on top of casing.

DYR
F&P
H&M
J&M
LJD
RLS
COMM

CEMENT VERIFICATION REQUIRED WITH PLUGGING REPORT

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Agent

DATE July 18, 1979

(This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DIRECTOR
O & G CONS. COMM.

DATE AUG 31 1979



00221790